

by longer-term contracts. The ISO will manage both ISO procured and self-provided Ancillary Services as part of the real-time Dispatch. The ISO will calculate payments for Ancillary Services to Scheduling Coordinators and charge the cost to Scheduling Coordinators.

For purposes of this ISO Tariff, Ancillary Services are: (i) Regulation, (ii) Spinning Reserve, (iii) Non-Spinning Reserve, (iv) Replacement Reserve, (v) Voltage Support, and (vi) Black Start capability. Bids for Non-Spinning Reserve and Replacement Reserve may be submitted by the Demand-side as well as by owners of Generation. Bids for Regulation, Spinning Reserve, Non-Spinning Reserve, and Voltage Support may be submitted by a Scheduling Coordinator for other non-generation resources that are capable of providing the specific service and that meet applicable Ancillary Service standards and technical requirements, as set forth in Sections 8.1 through 8.4, and are certified by the ISO to provide Ancillary Services. The provision of Regulation, Spinning Reserve, Non-Spinning Reserve, and Voltage Support by other non-generation resources is subject to the same requirements applicable to other providers of these Ancillary Services, as set forth in Sections 8.5 through 8.14. Identification of specific services in this ISO Tariff shall not preclude development of additional interconnected operation services over time. The ISO and Market Participants will seek to develop additional categories of these unbundled services over time as the operation of the ISO Controlled Grid matures.

8.2 Ancillary Services Standards.

All Ancillary Services shall meet the ISO's Ancillary Services standards.

8.2.1 Determination of Ancillary Service Standards.

The ISO shall set the required standard for each Ancillary Service necessary to maintain the reliable operation of the ISO Controlled Grid. Ancillary Services standards shall be based on WECC Minimum Operating Reliability Criteria (MORC), NERC and ISO Controlled Grid reliability requirements. The ISO Grid Operations Committee, in conjunction with the relevant reliability council (WECC), shall develop these Ancillary Services standards to determine reasonableness, cost effectiveness, and adherence to NERC and WECC standards. The standards developed by the ISO shall be used as a basis for determining the quantity and type of each Ancillary Service which the ISO requires to be available. These requirements and standards apply to all Ancillary Services whether self-provided or procured by the ISO.

8.2.2 Time-frame For Revising Ancillary Service Standards.

The ISO Grid Operations Committee and the ISO Technical Advisory Committee shall periodically undertake a review of the ISO Controlled Grid operation to determine any revision to the Ancillary Services standards to be used in the ISO Control Area. At a minimum the ISO Grid Operations Committee and the ISO Technical Advisory Committee shall conduct such reviews to accommodate

revisions to WECC and NERC standards. The ISO may adjust the Ancillary Services standards temporarily to take into account, among other things variations in system conditions, real-time Dispatch constraints, contingencies, and voltage and dynamic stability assessments. Where practicable, the ISO will provide notice, via the ISO Home Page, of any temporary adjustments to Ancillary Service standards by 6:00 p.m. two days ahead of the Trading Day to which the adjustment will apply. Periodic reviews by the ISO Grid Operations Committee or the ISO Technical Advisory Committee may include, but are not limited to: (a) analysis of the deviation between actual and forecast Demand; (b) analysis of patterns of unplanned Generating Unit Outages; (c) analysis of compliance with NERC and WECC Criteria; (d) analysis of operation during system disturbances; (e) analysis of patterns of shortfalls between Final Day-Ahead Schedules and actual Generation and Demand; and (f) analysis of patterns of unplanned transmission Outages.

8.2.3 Quantities of Ancillary Services Required.

For each of the Ancillary Services, the ISO shall determine the quantity and location of the Ancillary Service which is required and which must be under the direct Dispatch control of the ISO on an hourly basis each day. The ISO shall determine the quantities it requires as follows:

8.2.3.1 Regulation Service.

The ISO shall maintain sufficient Generating Units immediately responsive to AGC in order to provide sufficient Regulation service to allow the ISO Control Area to meet WECC and NERC control performance criteria by continuously balancing Generation to meet deviations between actual and scheduled Demand and to maintain interchange schedules. The quantity of Regulation capacity needed for each Settlement Period of the Day-Ahead Market and the Hour-Ahead Markets shall be determined as a percentage of the aggregate scheduled Demand for that Settlement Period.

(a) Regulation Percentage Determination. The exact percentage required for each Settlement Period of the Day-Ahead Market and the Hour-Ahead Markets shall be determined by the ISO based upon its need to meet the WECC and NERC control performance criteria.

(b) Publication of Estimated Regulation Percentage for Day-Ahead Market. In accordance with the requirements of Appendix Y, the ISO will publish on WEnet its estimate of the percentage it will use for determining the quantity of Regulation it requires for each Settlement Period of the Day-Ahead Market for that Trading Day.

(c) Publication of Estimated Regulation Percentage for Hour-Ahead Market. The ISO will publish on WEnet its estimate of the percentage it will use to determine the quantity of Regulation it requires for each Hour-Ahead Market.

(d) Additional Regulation Requirement. Additional Regulation capacity may be procured by the ISO for the real-time operating period if needed to meet the WECC and NERC control performance criteria.

8.2.3.2 Spinning And Non-Spinning Reserves.

The ISO shall maintain minimum contingency Operating Reserve made up of Spinning Reserve and Non-Spinning Reserve in accordance with WECC MORC criteria equal to (a) 5% of the Demand (except the Demand covered by firm purchases from outside the ISO Control Area) to be met by Generation from hydroelectric resources plus 7% of the Demand (except the Demand covered by firm purchases from outside the ISO Control Area) to be met by Generation from other resources, or (b) the single largest Contingency, if this is greater or (c) by reference to such more stringent criteria as the ISO may determine from time to time. The Spinning Reserve component of Operating Reserve shall be no less than one-half the Operating Reserve required for each Settlement Period of the Day-Ahead Market, the Hour-Ahead Market and the Real Time Market. When the level of Operating Reserve is determined by Demand, the ISO shall not maintain Operating Reserve with respect to Demand covered by firm purchases from outside the ISO Control Area. In addition, the ISO shall maintain Operating Reserve equal to the total amount of: (i) Interruptible Imports scheduled by Scheduling Coordinators for any hour and, (ii) on demand obligations of Scheduling Coordinators (i.e., the demand obligations to other entities or Control Areas that the Scheduling Coordinator is to provide from resources within the ISO Controlled Grid). Such additional Operating Reserve is the responsibility of the Scheduling Coordinator either scheduling

interruptible imports or with on demand obligations and such additional Operating Reserve must either be self-provided or purchased from the ISO by Scheduling Coordinators. To the extent such additional Operating Reserve is self-provided by a Scheduling Coordinator, it may consist entirely of Non-Spinning Reserve. To the extent that such additional Operating Reserve is not self-provided by a Scheduling Coordinator, the ISO will procure the necessary amounts of Operating Reserve, but not necessarily entirely from Non-Spinning Reserve.

8.2.3.3 Replacement Reserve.

The ISO needs sufficient Replacement Reserve to be available to allow restoration of dispatched Operating Reserve to its Set Point within sixty minutes. The ISO shall make its determination of the required quantity of Replacement Reserve based on:

- (a) historical analysis of the deviation between actual and Day-Ahead forecast Demand,
- (b) historical patterns of unplanned Generating Unit Outages,
- (c) historical patterns of shortfalls between Final Day-Ahead Schedules and actual Generation and Demand,
- (d) historical patterns of unexpected transmission Outages, and
- (e) such other factors affecting the ability of the ISO to maintain System Reliability as the ISO may from time to time determine.

The ISO shall have discretion to determine the quantity of Replacement Reserve it requires in each Zone.

8.2.3.4 Voltage Support.

The ISO shall determine on an hourly basis for each day the quantity and location of Voltage Support required to maintain voltage levels and reactive margins within WECC and NERC criteria using a power flow study based on the quantity and location of scheduled Demand. The ISO shall issue daily voltage schedules (Dispatch instructions) to Participating Generators, Participating TOs and UDCs, which are required to be maintained for ISO Controlled Grid reliability. All other Generating Units shall comply with the power factor requirements set forth in contractual arrangements in effect on the ISO Operations Date,

or, if no such contractual arrangements exist and the Generating Unit exists within the system of a Participating TO, the power factor requirements applicable under the Participating TO's TO Tariff or other tariff on file with the FERC.

All Participating Generators shall maintain the ISO specified voltage schedule at the transmission interconnection points to the extent possible while operating within the power factor range specified in their interconnection agreements or, for Regulatory Must-Take Generation, Regulatory Must-Run Generation and Reliability Must-Run Generation consistent with existing obligations. For Generating Units, that do not operate under one of these agreements, the minimum power factor range will be within a band of 0.90 lag (producing VARs) and 0.95 lead (absorbing VARs) power factors. Participating Generators with Generating Units existing at the ISO Operations Date that are unable to meet this operating power factor requirement may apply to the ISO for an exemption. Prior to granting such an exemption, the ISO shall require the Participating TO or UDC to whose system the relevant Generating Units are interconnected to notify it of the existing contractual requirements for Voltage Support established prior to the ISO Operations Date for such Generating Units. Such requirements may be contained in CPUC Electric Rule 21 or the Interconnection Agreement with the Participating TO or UDC. The ISO shall not grant any exemption under this Section from such existing contractual requirements. The ISO shall be entitled to instruct Participating Generators to operate their Generating Units at specified points within their power factor ranges. Participating Generators shall receive no compensation for operating within these specified ranges.

If the ISO requires additional Voltage Support, it shall procure this either through Reliability Must-Run Contracts or, if no other more economic sources are available by instructing a Generating Unit to move its MVar output outside its mandatory range. Only if the Generating Unit must reduce its MW output in order to comply with such an instruction will it be compensated in accordance with Section 8.5.9.

All Loads directly connected to the ISO Controlled Grid shall maintain reactive flow at grid interface points within a specified power factor band of 0.97 lag to 0.99 lead. Loads shall not be compensated for the service of maintaining the power factor at required levels within the bandwidth. A

UDC interconnecting with the ISO Controlled Grid at any point other than a Scheduling Point shall be subject to the same power factor requirement.

The power factor for both the Generating Units and Loads shall be measured at the interconnection point with the ISO Controlled Grid. The ISO will develop and will be authorized to levy penalties against Participating Generators, UDCs or Loads whose Voltage Support does not comply with the ISO's requirements. The ISO will establish voltage control standards with UDCs and the operators of other Control Areas and will enter into operational agreements providing for the coordination of actions in the event of a voltage problem occurring.

Wheeling Through and Wheeling Out transactions may also be subject to a reactive charge as developed by the ISO. If the ISO shall determine that a reactive charge should be payable at a future date, it shall, subject to FERC acceptance and approval, publish annually the Voltage Support obligations and applicable charges for Wheeling Through and Wheeling Out transactions at Scheduling Points. The obligations shall be predetermined by the ISO based on the estimated amount of the Wheeling Through and Wheeling Out transactions each year.

8.2.3.5 Black Start Capability.

The ISO shall determine the amount and location of Black Start Generation it requires through contingency studies that are used as the basis of the ISO's emergency plans. The studies shall specify:

- (a) the initiating disturbance;
- (b) the magnitude of the Outage, including the extent of the Outage (local area, ISO Controlled Grid, or WECC), the assumed status of Generation after the initiating disturbance, the status of interconnections, the system Demand level at the time of the disturbance, the interconnection support, and assumptions regarding the availability of support from other utilities to help restore Generation and Demand;
- (c) the Generator performance including a percentage of Black Start units (to be determined by the ISO) which are expected to fail to start, and;

(d) expected transmission system damage.

The ISO shall also specify the following load restoration performance goals:

- (i) Black Start unit startup and connection times;
- (ii) ISO Controlled Grid restoration times; and
- (iii) load restoration times.

Scheduling Coordinators shall provide the ISO with their load restoration time requirements for any Loads that provide emergency services.

8.2.3.6 The ISO, whenever possible, will increase its purchases of an Ancillary Service that can substitute for another Ancillary Service, when doing so is expected to reduce its total cost of procuring Ancillary Services while meeting reliability requirements. The ISO will make such adjustments in accordance with the following principles:

- (a) The Regulation requirement must be satisfied by Regulation bids from Resources qualified to provide Regulation;
- (b) Additional Regulation capacity can be used to satisfy requirements for any type of reserves (Spinning Reserve, Non-Spinning Reserve or Replacement Reserve);
- (c) Regulation and Spinning Reserve requirements must be satisfied by the combination of Regulation and Spinning Reserve bids. Spinning Reserve and Regulation may be provided as separate services from the same Generating Unit, provided that the sum of Spinning Reserve and Regulation provided is not greater than the maximum ramp rate of the Generating Unit (MW/minute) times ten;
- (d) Additional Regulation and Spinning Reserve capacity can be used to satisfy requirements for Non-Spinning and Replacement Reserve, except that any Spinning Reserve capacity that has been designated as available to supply Imbalance Energy only in the event of the occurrence of an unplanned Outage, a Contingency or an imminent or actual System Emergency cannot be used to satisfy requirements for Replacement Reserve;

- (e) Regulation, Spinning Reserve, Non-Spinning Reserve requirements must be satisfied by the combination of Regulation, Spinning Reserve and Non-Spinning Reserve bids;
- (f) Additional Regulation, Spinning Reserve, Non-Spinning Reserve, and Replacement Reserve capacity can be used to satisfy requirements for Replacement Reserve except that any Spinning and Non-Spinning Reserve capacity that has been designated as available to supply Imbalance Energy only in the event of the occurrence of an unplanned Outage, a Contingency or an imminent or actual System Emergency cannot be used to satisfy requirements for Replacement Reserve;
- (g) Total MW purchased from the Regulation, Spinning Reserve, Non-Spinning Reserve, and Replacement Reserve markets will not be changed by this Section 8.2.3.6; and
- (h) All quantities of Ancillary Services so procured must be non-negative.

8.2.4 Locational Quantities of Ancillary Services.

For each of the Ancillary Services, the ISO shall determine the required locational dispersion in accordance with ISO Controlled Grid reliability requirements. These standards shall be used as guidance only. The actual location of Ancillary Services on a daily and hourly basis shall depend on the locational spread of Demand within the ISO Control Area, the available transmission capacity, the locational mix of Generation, and historical patterns of transmission and Generation availability.

8.2.5 Black Start Units. The ISO will select Black Start capacity in locations where adequate transmission capacity can be made readily available (assuming no transmission damage) to connect the Black Start Generating Unit to the station service bus of a Generating Unit designated by the ISO. Black Start Units:

- (a) must be located in the ISO Control Area;
- (b) may be located anywhere in the ISO Control Area provided that the Black Start resource is capable of meeting the ISO performance requirements for starting and interconnection to the ISO Controlled Grid; but

(c) must be dispersed throughout the ISO Control Area.

8.2.5.1 Black Start Services.

(a) All Participating Generators with Black Start Generating Units must satisfy technical requirements specified by the ISO.

(b) The ISO shall from time to time undertake performance tests, with or without prior notification.

(c) The ISO shall have the sole right to determine when the operation of Black Start Generating Units is required to respond to conditions on the ISO Controlled Grid.

(d) If the ISO has intervened in the market for Energy and/or Ancillary Services pursuant to Section 7.4.4, the price paid by the ISO for Black Start services shall be sufficient to permit the relevant Participating Generator to recover its costs over the period that it is directed to operate by the ISO.

(e) If a Black Start Generating Unit fails to achieve a Black Start when called upon by the ISO, or fails to pass a performance test administered by the ISO, the Market Participant that has contracted to supply Black Start service from the Generating Unit shall re-pay to the ISO any reserve payment(s) that it has received since the administration of the last performance test or the last occasion upon which it successfully achieved a Black Start when called upon by the ISO, whichever is the shorter period.

8.3 Procurement of Ancillary Services, Certification and Testing Requirements for Providers of Ancillary Services, and Time-frame For Contracting for Ancillary Services.

8.3.1 Procurement of Ancillary Services.

Regulation, Operating Reserve, and Replacement Reserve necessary to meet ISO requirements not met by self-provision will be procured by the ISO as described in this ISO Tariff. As of the ISO Operations Date, the ISO will contract for long-term Voltage Support service with Owners of Reliability Must-Run Units under Reliability Must-Run Contracts. Black Start capability will initially be procured by the ISO through individual contracts with Scheduling Coordinators for Reliability Must-Run Units and other Generating Units which have Black Start capability. These requirements and standards apply to all Ancillary Services whether self-provided or procured by the ISO.

8.3.2 Procurement Not Limited to ISO Control Area.

The ISO will procure Spinning Reserves, Non-Spinning Reserves and Replacement Reserves from Generating Units operating within the ISO Control Area and from external imports of System Resources. Scheduling Coordinators are allowed to bid or self-provide their Regulation obligation in whole or in part from resources located outside the ISO Control Area by dynamically scheduling such resources. Each System Resource used to bid or self-provide Regulation must comply with the Dynamic Scheduling Protocol in Appendix X.

8.3.3 Certification and Testing Requirements.

Each Generating Unit, System Unit, Load, or System Resource that is allowed to bid or self-provide Ancillary Services under this Tariff must comply with the ISO's certification and testing requirements. Each Generating Unit and System Unit used to bid Regulation or used to self-provide Regulation must have been certified and tested by the ISO using the process defined in Part A of Appendix K, Each System Resource used to bid or self-provide Regulation must comply with the Dynamic Scheduling Protocol in Appendix X. Spinning Reserve may be provided only from Generating Units, System Resources from external imports, or System Units, which have been certified and tested by the ISO using the process defined in Appendix K, Non-Spinning Reserve and Replacement Reserve may be provided from Loads, Demand which can be reduced by Dispatch, interruptible exports, on-demand rights from other entities or Control Areas, Generating Units, System Resources from external imports, or System Units, which have been certified and tested by the ISO using the process defined in – Parts C & D of Appendix K, respectively, Voltage Support may only be provided from resources including Loads, Generating Units and System Units which have been certified and tested by the ISO using the process defined in Part E of Appendix K, Black Start capability may only be provided from Generating Units which have been certified and tested by the ISO using the process defined in Part F of Appendix K. ISO certification to provide ancillary services may be revoked by the ISO under the provisions of this Tariff and Parts A-F of Appendix K.

8.3.4 The ISO shall procure on a daily and hourly basis, each day, Regulation, Spinning, Non-Spinning and Replacement Reserves. The ISO shall procure Replacement Reserve on a longer-term basis pursuant to Section 42.1.3 if necessary to meet reliability criteria. The ISO Governing Board must approve all long-term Replacement Reserve contracts. The ISO shall contract for Voltage Support annually (or for such other period as the ISO may determine is economically advantageous) and on a daily or hourly basis as required to maintain System Reliability. The ISO shall contract annually (or for such other period as the ISO may determine is economically advantageous) for Black Start Generation.

8.4 Technical Requirements for Providing Ancillary Services.

All Generating Units, System Units, Loads and System Resources providing Ancillary Services shall comply with the technical requirements set out in Sections 8.4.1 to 8.4.6.1 below relating to their operating capabilities, communication capabilities and metering infrastructure. No Scheduling Coordinator shall be permitted to submit a bid to the ISO for the provision of an Ancillary Service from a Generating Unit, System Unit, Load or System Resource, or to submit a Schedule for self-provision of an Ancillary Service from that Generating Unit, System Unit, Load or System Resource, unless the Scheduling Coordinator is in possession of a current certificate issued by the ISO confirming that the Generating Unit, System Unit, Load or System Resource complies with the ISO's technical requirements for providing the Ancillary Service concerned. Scheduling Coordinators can apply for Ancillary Services certificates in accordance with the ISO's Protocols for considering and processing such applications. The ISO shall have the right to inspect Generating Units, Loads or the individual resources comprising System Units and other equipment for the purposes of the issue of a certificate and periodically thereafter to satisfy itself that its technical requirements continue to be met. If at any time the ISO's technical requirements are not being met, the ISO may withdraw the certificate for the Generating Unit, System Unit, Load or System Resource concerned.

8.4.1 Operating Characteristics Required to Provide Ancillary Services.

Each Generating Unit, System Unit, Load or System Resource which a Scheduling Coordinator wishes to schedule or bid to provide Ancillary Services must comply with the requirements for the specific Ancillary Service in regard to the following:

- (a) ramp rate increase and decrease (MW/minute);
- (b) power factor (leading and lagging) as required by Section 8.2.3.4;
- (c) maximum output (real and reactive), except that System Resources shall be required to comply only with the requirement for maximum real power;
- (d) minimum output (real and reactive), except that System Resources shall be required to comply only with the requirement for minimum real power;
- (e) AGC capability, control scheme, and range; and
- (f) minimum length of time the resource can be available to provide the relevant Ancillary Service.

The ISO will differentiate the operating characteristics according to the Ancillary Service being provided.

8.4.1.1 Regulation.

A Generating Unit offering Regulation must have the following operating characteristics and technical capabilities:

- (a) it must be capable of being controlled and monitored by the ISO Energy Management System (EMS) by means of the installation and use of a standard ISO direct communication and direct control system, a description of which and criteria for any temporary exemption from which, the ISO shall publish on the ISO internet "Home Page;"
- (b) it must be capable of achieving at least the ramp rates (increase and decrease in MW/minute) stated in its bid for the full amount of Regulation capacity offered;

- (c) the Regulation capacity offered must not exceed the maximum ramp rate (MW/minute) of that Unit times a value within a range from a minimum of ten minutes to a maximum of thirty minutes, which value shall be specified by the ISO and published on the ISO's internet "Home Page;"
- (d) the Generating Unit to ISO Control Center telemetry must in a manner meeting ISO standards include indications of whether the Generating Unit is on or off AGC at the Generating Unit terminal equipment;
- (e) the Generating Unit must be capable of the full range of movement within the amount of Regulation capability offered without manual Generating Unit operator intervention of any kind; and
- (f) each Participating Generator must ensure that the ISO EMS control and related SCADA equipment for its generating facility are operational throughout the time period during which Regulation is required to be provided.

8.4.1.2 Voltage Support.

A Generating Unit providing Voltage Support must be under the control of generator automatic voltage regulators throughout the time period during which Voltage Support is required to be provided. A Generating Unit may be required to operate underexcited (absorb reactive power) at periods of light system Demand to avoid potential high voltage conditions, or overexcited (produce reactive power) at periods of heavy system Demand to avoid potential low voltage conditions.

8.4.2 Ancillary Service Control Standards. The providers of ancillary services under this Tariff must comply with the following control standards:

- (a) Regulation. The ACE will be calculated by the ISO EMS. Control signals will be sent from the ISO EMS to raise or lower the output of Generating Units or System Resources providing Regulation when ACE exceeds the allowable ISO Control Area dead band for ACE;
- (b) Spinning and Non-Spinning Reserve. Each provider of Spinning Reserve or Non-Spinning Reserve must be capable of receiving a Dispatch instruction within one minute from the time the ISO Control Center elects to Dispatch the Spinning Reserve resource or Non-Spinning Reserve resource and

must ensure that its resource can be at the Dispatched operating level within ten minutes after issue of the Dispatch instruction;

(c) Replacement Reserve. Each provider of Replacement Reserve must be capable of receiving a Dispatch instruction within one minute from the time the ISO Control Center elects to Dispatch the Replacement Reserve resource and must ensure that its resource can be at the Dispatched operating level or condition within sixty minutes after issue of the Dispatch instruction;

(d) Voltage Support. Generating Units providing Voltage Support must have automatic voltage regulators which can correct the bus voltages to be within the prescribed voltage limits and within the machine capability in less than one minute; and

(e) Black Start. (i) Voice Communications: each supplier of Black Start capability must ensure that normal and emergency voice communications are available to permit effective Dispatch of the Black Start capability; (ii) ISO Confirmation: No load served by the Black Start Generating Unit or by any designated Generating Unit or by any transmission facility used for Black Start service may be restored until the ISO has confirmed that the need for such service has passed.

8.4.3 Ancillary Service Capability Standards. The providers of ancillary services under this Tariff must comply with the following capability standards

(a) Spinning and Non-Spinning Reserve Capability. Each Generating Unit or external import of a System Resource scheduled to provide Spinning Reserve and each resource providing Non-Spinning Reserve must be capable of converting the full capacity reserved to Energy production within ten minutes after the issue of the Dispatch instruction by the ISO, and of maintaining that output or scheduled interchange for at least two hours.

(b) Replacement Reserve. Each resource providing Replacement Reserve must be capable of supplying any level of output up to and including its full reserved capacity within sixty minutes after issue of Dispatch instructions by the ISO. Replacement Reserve may be supplied from resources already providing another Ancillary Service, such as Spinning Reserve, but only to the extent that the ability to provide the other Ancillary Service is not restricted in any way by the provision of Replacement Reserve.

The sum of Ancillary Service capacity supplied by the same resource cannot exceed the capacity of said resource.

(c) Black Start. Each Black Start Generating Unit must be able to start up with a dead primary and station service bus within ten minutes of issue of a Dispatch instruction by the ISO requiring a Black Start. Each Black Start Generating Unit must provide sufficient reactive capability to keep the energized transmission bus voltages within emergency voltage limits over the range of no-load to full load. Each Black Start Generating Unit must be capable of sustaining its output for a minimum period of 12 hours from the time when it first starts delivering Energy.

8.4.4 Ancillary Service Availability Standards. The providers of ancillary services under this Tariff must comply with the following availability standards.

(a) Spinning and Non-Spinning Reserve. Each Participating Generator shall ensure: (i) that its Generating Units scheduled to provide Spinning Reserve and Non-Spinning reserve are available for Dispatch throughout the Settlement Period for which they have been scheduled; and (ii) that its Generating Units scheduled to provide Spinning Reserve are responsive to frequency deviations throughout the Settlement Period for which they have been scheduled.

(b) Replacement Reserve. Each resource providing Replacement Reserve must be capable of sustaining the instructed output for at least two hours.

8.4.5 Communication Equipment.

Unless otherwise authorized by the ISO, all Scheduling Coordinators wishing to submit an Ancillary Service schedule or bid must have the capability to submit and receive information by direct computer link. In addition, they must be capable of receiving Dispatch instructions electronically and they must provide the ISO with a telephone number, or fax number through which Dispatch instructions for each Generating Unit, System Unit, Load and System Resource may be given if necessary. The ISO will determine which method of communication is appropriate; provided that the ISO will consult with the Scheduling Coordinator, if time permits, and will consider the method of communication then utilized by such Scheduling Coordinator; provided further, that the ISO shall make the final determination as to the

additional communication methods. Participating Generators, owners or operators of Loads and operators of System Units or System Resources whose resources are scheduled, bid in or under contract, shall ensure that there is a 24 hour personal point of contact with the ISO for the Generating Unit, System Unit, Load or System Resource. A Participating Generator or provider of Curtailable Demand wishing to offer any Ancillary Service must provide a direct ring down voice communications circuit (or a dedicated telephone line available 24 hours a day every day of the year) between the control room operator for the Generating Unit or Curtailable Demand providing the Ancillary Service and the ISO Control Center. Each Participating Generator must also provide an alternate method of voice communications with the ISO from the control room in addition to the direct communication link required above. Operators of System Resources from which dynamic schedules or bids are submitted to the ISO shall provide communications links meeting ISO standards for dynamic imports from System Resources. Participating Generators and operators of System Units providing Regulation shall also provide communication links meeting ISO standards for direct digital control. Operators of System Resources providing Regulation shall provide communications links meeting ISO standards for external imports of Regulation. If any communication system becomes unavailable, the relevant Participating Generators, operators of System Units, Loads and System Resources and the ISO shall take immediate action to identify the cause of the interruption and to restore the communication system. A Scheduling Coordinator that has scheduled or bid in or contracted for Ancillary Services shall ensure that the Generating Unit, System Unit, Load or System Resource concerned is able to receive and implement Dispatch Instructions.

8.4.6 Metering Infrastructure.

All Participating Generators, owners or operators of Loads and operators of System Units or System Resources which a Scheduling Coordinator wishes to schedule or bid to provide Ancillary Services shall have the metering infrastructure for the Generating Units, System Units, Loads or System Resources concerned which complies with requirements to be established by the ISO relating to:

- (a) meter type;
- (b) meter location;

- (c) meter reading responsibility;
- (d) meter capability in regard to AGC response; and
- (e) any other aspect of metering infrastructure required by the ISO under this ISO Tariff.

8.4.6.1 Additional Requirements for Black Start Units.

A Participating Generator who wishes to offer Black Start must ensure that the requirements set out in Appendix D to this ISO Tariff are met in relation to the Generating Units from which Black Start will be offered.

8.4.7 Methodology For Procurement of Ancillary Services Upon Commencement of ISO Operations.

8.4.7.1 Usage Charge in Ancillary Service Bid Evaluation.

Due to the design of the ISO's scheduling software, the ISO will not take into account Usage Charges in the evaluation of Ancillary Services bids or in price determination and, in the event of Congestion in the Day-Ahead Market or Hour-Ahead Market, Ancillary Services will be procured and priced on a Zonal basis.

8.4.7.2 Market-Based Prices.

Public utilities under the FPA must submit bids for Ancillary Services capped at FERC authorized cost-based rates unless and until FERC authorizes different pricing. Public utilities under the FPA shall seek FERC Ancillary Services rate approval on bases consistent with the ISO time-frame for contracting for each Ancillary Service (hourly rate for some Ancillary Services, annual rate or otherwise for other Ancillary Services) so that cost-based bids and market-based bids for each service shall be on comparable terms. All other entities may use market-based rates not subject to any restrictions apart from those found in this ISO Tariff. Public utilities under the FPA which have not been approved to bid at market-based rates, will not be paid above their cost-based bid for the Ancillary Service concerned even if the relevant Market Clearing Price is higher.

8.4.7.3 Bidding and Self-Provision of Ancillary Services.

The ISO will procure Ancillary Services in accordance with this ISO Tariff, and the applicable ISO Protocols.

8.4.7.3.1 Content of Ancillary Services Schedules and Bids.

Scheduling Coordinators may bid or self-provide Ancillary Services or specify Inter-Scheduling Coordinator Ancillary Service Trades from resources located within the ISO Control Area. Ancillary Services in the Day-Ahead Market and the Hour-Ahead Market are comprised of the following: Regulation, Spinning Reserve, Non-Spinning Reserve and Replacement Reserve. Each Generating Unit (including Physical Scheduling Plants), System Unit, Curtailable Demand or System Resource for which a Scheduling Coordinator wishes to submit Ancillary Services Schedules and bids must meet the requirements set forth in this ISO Tariff. The same resource capacity may be offered into more than one ISO Ancillary Service auction at the same time (the sequential evaluation of such multiple offers between Ancillary Services markets to eliminate double counting of capacity is described in the Section 8.5.5). In each category of Ancillary Service, the reference to "Revised" types of Schedules indicates a submittal which is part of a Revised Day-Ahead Schedule. Each of the following data sections can be submitted up to seven (7) days in advance. Ramp rates submitted as detailed below will be only used by the ISO for procuring capacity associated with the specific Ancillary Services. The ISO will issue real-time Dispatch Instructions for the Energy associated with the awarded capacity based upon the applicable operational ramp rate submitted with the single Energy Bid curve in accordance with Section 30.4.6. There is no provision for external exports with regard to Ancillary Services bids. The functionality necessary to accept such bids does not exist in the ISO scheduling software.

8.4.7.3.2 Scheduling Coordinators may bid or self-provide external imports of Spinning Reserve, Non-Spinning Reserve or Replacement Reserve from System Resources located outside the ISO Control Area including dynamically scheduled System Resources, where technically feasible and consistent with WECC criteria; and provided that such Scheduling Coordinators have certified to the ISO their ability to deliver the service to the point of interchange with the ISO Control Area (including with respect to their

ability to make changes, or cause such changes to be made, to interchange schedules during any interval of a Settlement Period at the discretion of the ISO).

8.4.7.3.3 Scheduling Coordinators may bid or self-provide external imports of Regulation from System Resources located outside the ISO Control Area, where technically feasible and consistent with WECC criteria by dynamic scheduling; provided that the operator of the Control Area in which the System Resources are located has entered into an agreement with the ISO for interconnected Control Area operations; and provided that such Scheduling Coordinator and the operator of the Control Area in which the resources are located have been certified by the ISO as to their ability to dynamically adjust interchange schedules based on control signals issued by the ISO anytime during a Settlement Period at the discretion of the ISO. Such certification shall include a demonstration of their ability to support the dynamic interchange of Regulation service based on ISO control signals received on dedicated communications links (either directly or through EMS computers) for ISO computer control and telemetry to provide this function in accordance with ISO standards and procedures posted on the ISO Home Page.

8.4.7.3.4 Scheduling Coordinators may utilize transmission service under Existing Contracts to self-provide Regulation (consistent with this ISO Tariff), from resources located outside the ISO Control Area, where technically feasible, consistent with WECC standards.

8.4.7.3.5 Scheduling Coordinators' bidding or self-provision of Ancillary Services according to this Section 8.4.7.3 shall be consistent with the ISO Protocols.

8.4.7.3.6 Due to the design of the ISO's scheduling system, any specific resource can bid to supply a specific Ancillary Service or can self-provide such Ancillary Service but cannot do both in the same Settlement Period.

8.5 The Bidding Process.

The ISO shall operate a competitive Day-Ahead and Hour-Ahead Market to procure Ancillary Services. It shall purchase Ancillary Services capacity at least cost to End-Use Customers consistent with maintaining System Reliability. Any Scheduling Coordinator representing Generating Units, System Units, Loads or external imports of System Resources may bid into the ISO's Ancillary Services market provided that it is

in possession of a current certificate for the Generating Units, System Units, external imports of System Resources or Loads concerned.

8.5.1 Provision of System Information to Scheduling Coordinators.

By 6:00 p.m. two days prior to the Trading Day, the ISO shall make available to Scheduling Coordinators general system information including those items of information set forth in Section 6.9.1. This information shall be provided at the same time as the ISO provides general system information to all Scheduling Coordinators wishing to schedule power on the ISO Controlled Grid.

8.5.2 Time Frame for Submitting And Evaluating Bids.

8.5.2.1 Day-Ahead Auction.

Bids for the ISO's Day-Ahead Regulation, Spinning Reserve, Non-Spinning Reserve and Replacement Reserve service market must be received by 10:00 am on the day prior to the Trading Day. The bids shall include information for each of the twenty-four (24) Settlement Periods of the Trading Day. Failure to provide the information within the stated time frame shall result in the bids being declared invalid by the ISO.

8.5.2.2 Hour-Ahead Auction. The ISO will require Scheduling Coordinators to honor their Day-Ahead Ancillary Services schedules and/or bids when submitting their Hour-Ahead Ancillary Services schedules and/or bids. Bids for the ISO's Hour-Ahead Regulation, Spinning Reserve, Non-Spinning Reserve and Replacement Reserve service market for each Settlement Period must be received at least two hours prior to the commencement of that Settlement Period. The bids shall include information for only the relevant Settlement Period. Failure to provide the information within the stated time frame shall result in the bids being declared invalid by the ISO. Scheduling Coordinators wishing to buy back in the Hour-Ahead Market Regulation, Spinning Reserve, Non-Spinning Reserve or Replacement Reserve capacity sold to the ISO in the Day-Ahead Market pursuant to Section 8.7 must do so by submitting a revised bid in the Hour-Ahead Market for the Ancillary Service and resource concerned.

8.5.3 Information to Be Submitted By Bidders.

8.5.3.1 Information for Use in Day-Ahead Market and Hour-Ahead Market.

Bids shall be submitted by Scheduling Coordinators acting on behalf of Participating Generators, and owners or operators of Loads. Bids must be in the format specified by the ISO and include the bid information for each service described in Sections 8.5.6 to 8.5.10 and such other information as the ISO may determine it requires to evaluate bids as published from time to time in this ISO Tariff or ISO Protocols. The ISO will verify and respond to submitted bid data in accordance with Appendix E and the ISO Protocols. Bidders may submit new bids on a daily basis (or hourly basis for the Hour-Ahead Market).

8.5.3.2 Information for Use in Real-Time Dispatch of Ancillary Services.

Scheduling Coordinators with Ancillary Services awards must submit a single Energy Bid curve in the Real Time Market to correspond to any awarded capacity for the relevant resources Scheduling Coordinators must submit Energy Bids for resources providing Spinning, Non-Spinning, or Replacement Reserves.

8.5.4 Bid Evaluation Rules.

Bid evaluation shall be based on the following principles:

- (a) the ISO shall not differentiate between bidders other than through price and capability to provide the service, and the required locational mix of services;
- (b) to minimize the costs to users of the ISO Controlled Grid, the ISO shall select the bidders with lowest bids for capacity which meet its technical requirements, including location and operating capability;
- (c) for the Day-Ahead Market, the Day-Ahead bids shall be evaluated independently for each of the 24 Settlement Periods of the following Trading Day;
- (d) for the Hour-Ahead Market, the ISO shall evaluate bids in the two hours preceding the hour of operation;

(e) the ISO will procure sufficient Ancillary Services in the Day-Ahead Market to meet its forecasted requirements, as known at the close of the Day-Ahead Market, except that the ISO may elect to procure a portion of such requirements in the Hour-Ahead Markets if the ISO first provides notice to Scheduling Coordinators of such action, including the approximate hourly megawatt amounts of each Ancillary Service that it intends to procure in the Hour-Ahead Markets;

(f) the ISO will (to the extent available) procure sufficient Ancillary Services to meet its requirements;
and

(g) the ISO will evaluate and price only those Ancillary Services bids received.

8.5.5 Evaluation of Ancillary Services Bids.

When Scheduling Coordinators bid into the Regulation, Spinning Reserve, Non-Spinning Reserve and Replacement Reserve markets, they may bid the same capacity into as many of these markets as desired at the same time by providing the appropriate bid information to the ISO. The ISO shall evaluate bids in the markets for Regulation, Spinning Reserve, Non-Spinning Reserve and Replacement Reserve sequentially and separately in the following order: Regulation, Spinning Reserve, Non-Spinning Reserve and Replacement Reserve. Any capacity accepted by the ISO in one of these markets shall not be passed on to another market, except that capacity accepted in the Regulation market that represents the downward range of movement accepted by the ISO may be passed on to another market; any losing bids in one market may be passed onto another market, if the Scheduling Coordinator so indicates to the ISO. A Scheduling Coordinator may specify capacity bid into only the markets it desires. A Scheduling Coordinator shall also have the ability to specify different capacity prices and different Energy prices for the Spinning Reserve, Non-Spinning Reserve, Replacement Reserve and Regulation markets. The bid information, bid evaluation and price determination rules set forth below shall be used in the Day-Ahead, Hour-Ahead and real-time procurement of Regulation, Spinning Reserve, Non-Spinning Reserve, and Replacement Reserve.

A Scheduling Coordinator providing one or more Regulation, Spinning Reserve, Non-Spinning Reserve, and Replacement Reserve services may not change the identification of the Generating Units or

Loads offered in the Day-Ahead Market, the Hour-Ahead Market or in real time for such services unless specifically approved by the ISO (except with respect to System Units, if any, in which case Scheduling Coordinators are required to identify and disclose the resource specific information for all Generating Units and Curtailable Demands constituting the System Unit scheduled or bid into the ISO's Day-Ahead Market and Hour-Ahead Market as required in SP 3.3.2(e) in Appendix Y).

8.5.5.1 Ancillary Service Bid Evaluation and Pricing Terminology.

Unless otherwise specifically described herein, the following terminology will apply:

$CapRes_{ijt}$	=	the Ancillary Service reserve reservation bid price (in \$/MW).
Cap_{ijtmax}	=	the maximum amount of reserve that can be scheduled by the ISO with respect to a Scheduling Coordinator's bid of that resource to supply Ancillary Services (in MW).
Cap_{ij}	=	that portion of an Ancillary Services bid (in MW), identified in the ISO's evaluation process, that may be used to meet the ISO's Requirement for a particular Ancillary Service ($Cap_{ijt} < Cap_{ijtmax}$)
Requirement	=	the total amount of reserve that must be scheduled for a particular Ancillary Service required by the ISO in a Settlement Period (in MW).
i, j, t	=	Generating Unit i , Scheduling Coordinator j , Settlement Period t .

8.5.6 The Regulation Auction.

Bid Information. Each Scheduling Coordinator j desiring to participate in the ISO's Regulation auction will submit the following information for each relevant Generating Unit or System Unit i for each Settlement Period t of the relevant Trading Day:

- (a) bidder name/Identification Code and Scheduling Coordinator's ID code;
- (b) resource identification (name and Location Code);

- (c) the date for which the bid applies;
- (d) maximum operating level (MW);
- (e) minimum operating level (MW);
- (f) ramp rate (MW/Min) $Ramp_{ijt}$;
- (g) the upward and downward range of generating capacity over which Generating Unit or System Unit i from Scheduling Coordinator j is willing to provide Regulation for Settlement Period t ($Cap_{ijt}max$ (MW) where $Cap_{ijt}max \leq Period_{minutes} * Ramp_{ijt}$. $Period_{minutes}$ is established by the ISO, by giving Scheduling Coordinators twenty-four (24) hours advance notice, within a range from a minimum of 10 minutes to a maximum of 30 minutes. Bidders shall offer upward and downward range for Regulation service;
- (h) the bid price of the capacity reservation, stated separately for Regulation Up and Regulation Down ($CapRes_{ijt}$ (\$/MW));
- (i) type of schedule: Regulation Ancillary Service (ANC_SRVC) or Revised Regulation Ancillary Service (REVISED_ANC_SRVC);
- (j) type of market (Day-Ahead or Hour-Ahead) and Trading Day;
- (k) preferred bid flag, a "YES" indicates a bid and a "NO" indicates a self-provided schedule; and
- (l) upward and downward range of Generating Unit or System Unit capacity over which the Generating Unit or System Unit is offering to provide Regulation.

Each Scheduling Coordinator desiring to participate in the ISO's Regulation auction will submit the following information for each relevant external import for each Settlement Period of the relevant Trading Day:

- (a) bidder name/Identification Code and Scheduling Coordinator's ID code;
- (b) type of market (Day-Ahead or Hour-Ahead) and Trading Day;
- (c) Scheduling Point (the name);

- (d) interchange ID code(the name of the selling entity, buying entity and a numeric identifier);
- (e) external Control Area ID;
- (f) Schedule ID (NERC ID number) and complete WECC tag;
- (g) preferred bid flag, a "YES" indicates a bid and a "NO" indicates a self-provided schedule;
- (h) the contract reference number, if applicable,
- (i) maximum operating level (MW);
- (j) minimum operating level (MW);
- (k) ramp rate (MW/Min) $Ramp_{ijt}$;
- (l) the upward and downward range of generating capacity over which System Resource i from Scheduling Coordinator j is willing to provide Regulation for Settlement Period t ($Cap_{ijt,max}$ (MW)) where $Cap_{ijt,max} \leq Period_{minutes} * Ramp_{ijt}$. $Period_{minutes}$ is established by the ISO, by giving Scheduling Coordinators twenty-four (24) hours advance notice, within a range from a minimum of 10 minutes to a maximum of 30 minutes. Bidders shall offer upward and downward range for Regulation service;
- (m) the bid price of the capacity reservation, stated separately for Regulation Up and Regulation Down ($CapRes_{ijt}$ (\$/MW)); and
- (n) type of schedule: (Regulation Ancillary Service).

Bid Evaluation. Based on the quantity and location of the system requirements, the ISO shall select Generating Units, System Units, and System Resources with the bids, which minimize the sum of the total bids of the Generating Units, System Units, and System Resources selected for Regulation Up or Regulation Down, subject to two constraints:

- (a) the sum of the selected bid capacities must be greater than or equal to the required Regulation capacity; and

- (b) each Generating Unit's, System Unit's, or System Resource's bid capacity must be less than or equal to that Generating Unit's, System Unit's, or System Resource's ramp rate times $\text{Period}_{\text{minutes}}$ where $\text{Period}_{\text{minute}}$ is established by the ISO, by giving Scheduling Coordinators twenty-four (24) hours advance notice, within a range from a minimum of 10 minutes to a maximum of 30 minutes.

The total bid for each Generating Unit, System Unit, or System Resource is calculated by multiplying the capacity reservation bid price by the bid capacity.

Thus, subject to any locational requirements, the ISO will accept winning Regulation bids in accordance with the following criteria:

$$\text{Min} \sum_{i,j} \text{TotalBid}_{ijt}$$

Subject to

$$\sum_{i,j} \text{Cap}_{ijt} \geq \text{Requirement}_t \text{ and } \text{Cap}_{ijt} \leq \text{Cap}_{ij\text{max}}$$

Where

$$\text{TotalBid}_{ijt} = \text{CapRes}_{ijt} * \text{Cap}_{ijt}$$

Requirement_t = Amount of upward and downward movement capacity required

Price Determination. The price payable to Scheduling Coordinators for Regulation Capacity made available for upward and downward movement in accordance with the ISO's Final Day-Ahead Schedules shall, for each Generating Unit, System Unit, and System Resource concerned, be the Zonal Market Clearing Price as follows:

$$\text{PAGC}_x = \text{MCP}_{xt}$$

Where:

The Zonal Market Clearing Price (MCP_{xt}) is the highest priced winning Regulation capacity bid in Zone X based on the capacity reservation bid price, i.e.

$$MCP_{xt} = \text{Max} (CapRes_{ijt}) \text{ in Zone } x \text{ for Settlement Period } t$$

In the absence of Inter-Zonal Congestion, the Zonal Market Clearing Prices will be equal.

The ISO's auction does not compensate the Scheduling Coordinator for the minimum Energy output of Generating Units, System Units, or System Resources bidding to provide Regulation. Therefore, disposition of any minimum Energy associated with Regulation selected in the ISO's Ancillary Services markets is the responsibility of the Scheduling Coordinator selling the Regulation.

The price payable to Scheduling Coordinators for Regulation capacity not included in the ISO's Final Day-Ahead Schedules but made available in accordance with amended Ancillary Services supplier schedules issued in accordance with Section 8.7 shall be the bid price of the Regulation Capacity reserved ($CapRes_{ijt}$ (\$/MW)).

8.5.7 The Spinning Reserve Auction.

Bid Information. If the bid is for the provision of Spinning Reserve from a Generating Unit or System Unit, each Scheduling Coordinator j must submit the following information for each Generating Unit or System Unit i for each Settlement Period t of the following Trading Day:

- (a) bidder name/Identification Code;
- (b) resource identification (name and Location Code);
- (c) the date for which the bid applies;
- (d) maximum operating level (MW);
- (e) minimum operating level (MW);
- (f) ramp rate (MW/min);

- (g) MW additional capability synchronized to the system, immediately responsive to system frequency, and available within 10 minutes (Cap_{ijtmax}) for Generating Unit i, or System Unit I, from Scheduling Coordinator j, for Settlement Period t;
- (h) bid price of capacity reserved ($CapRes_{ijt}$ (\$/MW));
- (i) an indication whether the capacity reserved would be available to supply Imbalance Energy only in the event of the occurrence of an unplanned Outage, a Contingency or an imminent or actual System Emergency;
- (j) type of schedule: Spinning Reserve Ancillary Service (ANC_SRVC) or Revised Spinning Reserve Ancillary Service (REVISED_ANC_SRVC);
- (k) type of market (Day-Ahead or Hour-Ahead) and Trading Day;
- (l) preferred bid flag, a "YES" indicates a bid and a "NO" indicates a self-provided schedule; and
- (m) Spinning Reserve capacity (MW).

If the bid is for the provision of Spinning Reserve from an external import of a System Resource, each Scheduling Coordinator j must submit the following information for each external import of a System Resource i for each Settlement Period t of the following Trading Day:

- (a) bidder name/Identification Code;
- (b) the date for which the bid applies;
- (c) ramp rate if applicable (MW/Min);
- (d) MW additional capability synchronized to the system, immediately responsive to system frequency and available at the point of interchange with the ISO Control Area, within 10 minutes (Cap_{ijtmax}) of the ISO calling for the external import of System Resource i, from Scheduling Coordinator j, for Settlement Period t;
- (e) bid price of capacity reserved ($CapRes_{ijt}$ (\$/MW));

- (f) an indication whether the capacity reserved would be available to supply Imbalance Energy only in the event of the occurrence of an unplanned Outage, a Contingency or an imminent or actual System Emergency; and, for a dynamic import of a System Resource, the following additional information:
 - (g) type of market (Day-Ahead or Hour-Ahead) and Trading Day;
 - (h) Scheduling Point (the name);
 - (i) interchange ID code(the name of the selling entity, buying entity and a numeric identifier);
 - (j) external Control Area ID;
 - (k) Schedule ID (NERC ID number) and complete WECC tag;
 - (l) preferred bid flag, a "YES" indicates a bid and a "NO" indicates a self-provided schedule;
 - (m) the contract reference number, if applicable;
 - (n) type of schedule: Spinning Reserve Ancillary Service (ANC_SRVC) or Revised Spinning Reserve Ancillary Service (REVISED_ANC_SRVC);
 - (o) export flag, a "YES" indicates an external export and a "NO" indicates an external import; and
 - (p) Spinning Reserve capacity (MW).

Bid Evaluation. Based on the quantity and location of the system requirements, the ISO shall select the Generating Units, System Units and external imports of System Resources with the bids which minimize the sum of the total bids of the Generating Units, System Units and external imports of System Resources selected subject to two constraints:

- (a) the sum of the selected bid capacities must be greater than or equal to the required Spinning Reserve capacity; and
- (b) each Generating Unit's, System Unit's or external import's bid capacity must be less than or equal to that Generating Unit's, System Unit's or external import's ramp rate times 10 minutes.

The total bid for each Generating Unit, System Unit or external import of a System Resource is calculated by multiplying the capacity reservation bid price by the bid capacity. Thus, subject to any locational requirements, the ISO will select the winning Spinning Reserve bids in accordance with the following criteria:

$$\text{Min} \sum_{i,j} \text{Totalbid}_{ijt}$$

Subject to

$$\sum_{i,j} \text{Cap}_{ijt} \geq \text{Requirement}_t$$

and $\text{Cap}_{ijt} \leq \text{Cap}_{ijtmax}$

Where

$$\text{TotalBid}_{ijt} = \text{Cap}_{ijt} * \text{CapRes}_{ijt}$$

Requirement_t = the amount of Spinning Reserve capacity required

Price Determination. The price payable to Scheduling Coordinators for Spinning Reserve Capacity made available in accordance with the ISO's Final Day-Ahead Schedules shall, for each Generating Unit or external import of a System Resource concerned be the Zonal Market Clearing Price for Spinning Reserve calculated as follows:

$$P_{sp_{xt}} = MCP_{xt}$$

Where the Zonal Market Clearing Price (MCP_{xt}) for Spinning Reserve is the highest priced winning Spinning Reserve capacity bid in Zone X based on the capacity reservation bid price, i.e.:

$$MCP_{xt} = \text{Max}(\text{CapRes}_{ijt}) \text{ in Zone } x \text{ for Settlement Period } t$$

In the absence of Inter-Zonal Congestion, the Zonal Market Clearing Prices will be equal.

The ISO's auction does not compensate a Scheduling Coordinator for the minimum Energy output of Generating Units, System Units or System Resources bidding to provide Spinning Reserve.

Therefore, any minimum Energy output associated with Spinning Reserve selected in the ISO's auction is the responsibility of the Scheduling Coordinator selling the Spinning Reserve.

The price payable to Scheduling Coordinators for Spinning Reserve Capacity not included in the ISO's Final Day-Ahead Schedules but made available in accordance with amended Ancillary Services supplier schedules issued in accordance with Section 8.7 shall be the bid price of the Spinning Reserve capacity reserved ($CapRes_{ijt}(\$/MW)$).

8.5.8 The Non-Spinning Reserve Auction.

Bid information. If the bid is for the provision of Non-Spinning Reserve from a Generating Unit or System Unit, each Scheduling Coordinator j must submit the following information for each Generating Unit or System Unit i for each Settlement Period t of the following Trading Day:

- (a) bidder name/Identification Code;
- (b) Generating Unit or System Unit identification (name and Location Code);
- (c) the date for which the bid applies;
- (d) maximum operating level (MW);
- (e) minimum operating level (MW);
- (f) ramp rate (MW/Min);
- (g) the MW capability available within 10 minutes (Cap_{ijtmax});
- (h) the bid price of the capacity reserved ($CapRes_{ijt}(\$/MW)$);
- (i) time to synchronization following notification (min);
- (j) an indication whether the capacity reserved would be available to supply Imbalance Energy only in the event of the occurrence of an unplanned Outage, a Contingency or an imminent or actual System Emergency;

- (k) type of schedule: Non-Spinning Reserve Ancillary Service (ANC_SRVC) or Revised Non-Spinning Reserve Ancillary Service (REVISED_ANC_SRVC);
- (l) type of market (Day-Ahead or Hour-Ahead) and Trading Day; and
- (m) preferred bid flag, a "YES" indicates a bid and a "NO" indicates a self-provided schedule.

If the bid is for the provision of Non-Spinning Reserve from an external import of a System Resource, each Scheduling Coordinator j must submit the following information for each external import of a System Resource i for each Settlement Period t of the following Trading Day:

- (a) bidder name/Identification Code;
- (b) the date for which the bid applies;
- (c) ramp rate if applicable (MW/Min);
- (d) the MW capability available at the point of interchange with the ISO Control Area, within 10 minutes (Cap_{ijtmax}) of the ISO calling for the external import of System Resource i , from Scheduling Coordinator j , for Settlement Period t ;
- (e) the bid price of the capacity reserved ($CapRes_{ijt}(\$/MW)$);
- (f) an indication whether the capacity reserved would be available to supply Imbalance Energy only in the event of the occurrence of an unplanned Outage, a Contingency or an imminent or actual System Emergency; and, for a dynamic import of a System Resource, the following additional information:
 - (g) type of market (Day-Ahead or Hour-Ahead) and Trading Day;
 - (h) Scheduling Point (the name);
 - (i) interchange ID code (the name of the selling entity, buying entity and a numeric identifier);
 - (j) external Control Area ID;
 - (k) Schedule ID (NERC ID number) and complete WECC tag;

- (l) preferred bid flag, a "YES" indicates a bid and a "NO" indicates a self-provided schedule;
- (m) the contract reference number, if applicable;
- (n) type of schedule: Non-Spinning Reserve Ancillary Service (ANC_SRVC) or Revised Non-Spinning Reserve Ancillary Service (REVISED_ANC_SRVC);
- (o) export flag, a "YES" indicates an external export and a "NO" indicates an external import; and
- (p) Non-Spinning Reserve capacity (MW).

If the bid is for the provision of Non-Spinning Reserve from a Load located within the ISO Control Area, each Scheduling Coordinator j must submit the following information for each Load i for each Settlement Period t of the following Trading Day:

- (a) bidder name/Identification Code;
- (b) Load identification name and Location Code;
- (c) the date for which the bid applies;
- (d) Demand reduction available within 10 minutes ($Cap_{ijt}max$);
- (e) to interruption following notification (min);
- (f) maximum allowable curtailment duration (hr);
- (g) the bid price of the capacity reserved ($CapRes_{ijt}(\$/MW)$);
- (h) an indication whether the capacity reserved would be available for Demand reduction only in the event of the occurrence of an unplanned Outage, a Contingency or an imminent or actual System Emergency;
- (i) type of schedule: Non-Spinning Reserve Ancillary Service (ANC_SRVC) or Revised Non-Spinning Reserve Ancillary Service (REVISED_ANC_SRVC);
- (j) type of market (Day-Ahead and Hour-Ahead) and Trading Day; and
- (k) preferred bid flag, a "YES" indicates a bid and a "NO" indicates a self-provided schedule.

Bid Evaluation. Based on the quantity and location of the system requirements, the ISO shall select the Generating Units, System Units, Loads or external imports of System Resources with the bids which minimize the sum of the total bids of the Generating Units, System Units, Loads or external imports of System Resources selected subject to two constraints:

- (a) the sum of the selected bid capacities must be greater than or equal to the required Non-Spinning Reserve capacity; and
- (b) each Generating Unit's, System Unit's, Load's or external import's bid capacity must be less than or equal to that Generating Unit's, System Unit's, Load's or external import's ramp rate (or time to interruption in the case of a Load offering Demand reduction) times the difference between 10 minutes and the time to synchronize in the case of a Generating Unit or System Unit or to interruption in the case of a Load. The total bid for each Generating Unit, System Unit, Load or external import of a System Resource is calculated by multiplying the capacity reservation bid by the bid capacity.

Thus subject to any locational requirements, the ISO will accept the winning Non-Spinning Reserve bids in accordance with the following criteria:

$$\text{Min} \sum_{i,j} \text{Totalbid}_{ijt}$$

Subject to

$$\sum_{i,j} \text{Cap}_{ijt} \geq \text{Requirement}_t$$

$$\text{Cap}_{ijt} \leq \text{Cap}_{ijt} \text{max}$$

Where

$$\text{TotalBid}_{ijt} = \text{Cap}_{ijt} * \text{CapRes}_{ijt}$$

Requirement_t = the amount of Non-Spinning Reserve capacity required

Price Determination. The price payable to Scheduling Coordinators for Non-Spinning Reserve Capacity made available in accordance with the ISO's Final Day-Ahead Schedules shall for each

Generating Unit, System Unit, Load or external import of a System Resource concerned be the Zonal Market Clearing Price for Non-Spinning Reserve calculated as follows:

$$P_{nonsp_{xt}} = MCP_{xt}$$

Where the Zonal Market Clearing Price (MCP_{xt}) for Non-Spinning Reserve is the highest priced winning Non-Spinning Reserve bid in Zone X based on the capacity reservation bid price, i.e.:

$$MCP_{xt} = \text{Max}(CapRes_{ijt}) \text{ in Zone } x \text{ for Settlement Period } t.$$

In the absence of Inter-Zonal Congestion, the Zonal Market Clearing Prices will be equal.

The price payable to Scheduling Coordinators for Non-Spinning Reserve Capacity not included in the ISO's Final Day-Ahead Schedules but made available in accordance with amended Ancillary Services supplier schedules issued in accordance with Section 8.7 shall be the bid price of the Non-Spinning Capacity reserved ($CapRes_{ijt}(\$/MW)$).

8.5.8A The Replacement Reserve Auction.

Bid Information. If the bid is for the provision of Replacement Reserve from a Generating Unit or System Unit each Scheduling Coordinator j must submit the following information for each Generating Unit or System Unit i for each Settlement Period t of the following Trading Day:

- (a) bidder name/Identification Code;
- (b) Generating Unit or System Unit identification (name and Location Code);
- (c) the date for which the bid applies;
- (d) maximum operating level (MW);
- (e) minimum operating level (MW);
- (f) ramp rate (MW/Min);
- (g) the MW capacity available within 60 minutes (Cap_{ijtmax});
- (h) the bid price of the capacity reserved ($CapRes_{ijt}(\$/MW)$);

- (i) time to synchronize following notification (min).
- (j) type of schedule: Replacement Reserve Ancillary Service (ANC_SRVC) or Revised Replacement Reserve Ancillary Service (REVISED_ANC_SRVC);
- (k) type of market (Day-Ahead or Hour-Ahead) and Trading Day; and
- (l) preferred bid flag, a "YES" indicates a bid and a "NO" indicates a self-provided schedule.

If the bid is for the provision of Replacement Reserve from an external import of a System Resource, each Scheduling Coordinator j must submit the following information for each external import of a System Resource i for each Settlement Period t of the following Trading Day:

- (a) bidder name/Identification Code;
- (b) the date for which the bid applies;
- (c) ramp rate applicable (MW/Min);
- (d) the MW capability available at the point of interchange with the ISO Control Area, within 60 minutes (Cap_{ijtmax}) of the ISO calling for the external import of System Resource i, from Scheduling Coordinator j, for Settlement Period t;
- (e) bid price of capacity reserved ($CapRes_{ijt}(\$/MW)$); and, for a dynamic import of a System Resource, the following additional information:
 - (h) type of market (Day-Ahead or Hour-Ahead) and Trading Day;
 - (i) Scheduling Point (the name);
 - (j) interchange ID code (the name of the selling entity, buying entity and a numeric identifier);
 - (k) external Control Area ID;
 - (l) Schedule ID (NERC ID number) and complete WECC tag;
- (m) preferred bid flag, a "YES" indicates a bid and a "NO" indicates a self-provided schedule;
- (n) the contract reference number, if applicable;

- (o) type of schedule: Replacement Reserve Ancillary Service (ANC_SRVC) or Revised Replacement Reserve Ancillary Service (REVISED_ANC_SRVC);
- (p) time to synchronize following notification (less than sixty (60) minutes mandatory); and
- (q) Replacement Reserve capacity (MW).

If the bid is for the provision of Replacement Reserve from a Load located within the ISO Control Area, each Scheduling Coordinator j must submit the following information for each Load i for each Settlement Period t of the following Trading Day:

- (a) bidder name/Identification Code;
- (b) Load identification (name and Location Code);
- (c) the date for which the bid applies;
- (d) the Demand reduction available within 60 minutes (Cap_{ijt} (MW));
- (e) time to interruption following notification (min);
- (f) maximum allowable curtailment duration (hr);
- (g) the bid price of the capacity reserved ($CapRes_{ijt}$ (\$/MW));
- (h) type of schedule: Replacement Reserve Ancillary Service (ANC_SRVC) or Revised Replacement Reserve Ancillary Service (REVISED_ANC_SRVC);
- (i) type of market (Day-Ahead or Hour-Ahead) and Trading Day;
- (j) preferred bid flag, a "YES" indicates a bid and a "NO" indicates a self-provided schedule; and
- (k) Curtailable Demand reduction rate (MW/minute).

Bid Evaluation. Based on the quantity and location of the system requirements, the ISO shall select the Generating Units, System Units, Loads or external imports of System Resources with the bids which minimize the sum of the total bids of the Generating Units, System Units, Loads or external imports of System Resources selected subject to two constraints:

- (a) the sum of the selected bid capacities must be greater than or equal to the required Replacement Reserve capacity; and
- (b) each Generating Unit's, System Unit's, Load's or external import's bid capacity must be less than or equal to that Generating Unit's, System Unit's, Load's or external import's ramp rate (or time to interruption in the case of a Load offering Demand reduction) times the difference between 60 minutes and the time to synchronize in the case of Generating Unit or System Unit, or to interruption in the case of Load.

The total bid for each Generating Unit, System Unit, Load or external import of System Resource is calculated by multiplying the capacity reservation bid price by the bid capacity.

Thus, subject to any locational requirements, the ISO will select the winning Replacement Reserve bids in accordance with the following criteria:

$$\text{Min} \sum_{i,j} \text{Totalbid}_{ijt}$$

Subject to

$$\sum_{i,j} \text{Cap}_{ijt} \geq \text{Requirement}_t$$

$$\text{Cap}_{ijt} \leq \text{Cap}_{ijtmax}$$

Where

$$\text{TotalBid}_{ijt} = \text{Cap}_{ijt} * \text{CapRes}_{ijt}$$

Requirement_t = the amount of Replacement Reserve capacity required

Price Determination. The price payable to Scheduling Coordinators for Replacement Reserve Capacity made available in accordance with the ISO's Final Day-Ahead Schedules shall, for each Generating Unit, System Unit, Load or external import of a System Resource concerned, be the Zonal Market Clearing Price for Replacement Reserve calculated as follows:

$$P_{\text{RepRes}_{xt}} = \text{MCP}_{xt}$$

Where the Zonal Market Clearing Price (MCP_{xt}) for Replacement Reserve is the highest priced winning Replacement Reserve bid in Zone X based on the capacity reservation bid price, i.e.:

$$MCP_{xt} = \text{Max}(CapRes_{ijt}) \text{ in Zone } x \text{ for Settlement Period } t.$$

In the absence of Inter-Zonal Congestion, the Zonal Market Clearing Prices will be equal.

The price payable to Scheduling Coordinators for Replacement Reserve Capacity not included in the ISO's Final Day-Ahead Schedules but made available in accordance with amended Ancillary Services schedules issued in accordance with Section 8.7 shall be the bid price of the Replacement Reserve capacity reserved ($CapRes_{ijt}(\$/MW)$).

8.5.9 Voltage Support.

As of the ISO Operations Date, the ISO will contract for Voltage Support service with the owners of Reliability Must-Run Units. Payments for public utilities under the FPA shall be capped at the FERC authorized cost-based rates unless and until FERC authorizes different pricing. The ISO shall pay owners of Reliability Must-Run Units for long-term Voltage Support through their Scheduling Coordinators.

In addition, any Participating Generator who is producing Energy shall, upon the ISO's specific request, provide reactive energy output outside the Participating Generator's Voltage Support obligation defined in Section 8.2.3.4.

The ISO shall select Participating Generator's Generating Units which have been certified for Voltage Support to provide this additional Voltage Support. Subject to any locational requirements, the ISO shall select the least costly Generating Units from a computerized merit order stack to back down to produce additional Voltage Support in each location where Voltage Support is needed.

The ISO shall pay to the Scheduling Coordinator for that Participating Generator the opportunity cost of reducing Energy output to enable reactive energy production. This opportunity cost shall be:

$\text{Max}\{0, \text{Zonal Settlement Interval Ex Post Price} - \text{Generating Unit bid price}\} \times \text{reduction in Energy output (MW)}$.

If necessary, the ISO shall develop a regulatory cost-based determination of marginal operating cost to be used in place of the Generating Unit bid price.

8.5.10 Black Start Capability and Energy Output.

As of the ISO Operations Date, the ISO will contract for Black Start capability and Energy with owners of Reliability Must-Run Units and Black Start Generators. Public utilities under the FPA will be paid rates capped at the FERC authorized cost base rates unless and until FERC authorizes different pricing.

The ISO shall pay owners of Reliability Must-Run Units for Black Start Energy output through their Scheduling Coordinators. The ISO shall pay Black Start Generators for Black Start Energy output directly.

8.6 Obligations for and Self-Provision of Ancillary Services.

8.6.1 Ancillary Service Obligations.

Each Scheduling Coordinator shall be assigned a share of the total Regulation, Spinning Reserve, Non-Spinning and Replacement Reserve requirements by the ISO. Any references in this Tariff to the Ancillary Service "Regulation" shall be read as referring to "Regulation Up" or "Regulation Down". The share assigned to each Scheduling Coordinator is described in Section 8.6 and in Section 8.12 as that Scheduling Coordinator's obligation. Each Scheduling Coordinator's Regulation obligation in each Zone shall be pro rata based upon the same proportion as the Scheduling Coordinator's metered hourly Demand (excluding exports) bears to the total metered Demand (excluding exports) served in each hour in that Zone. Each Scheduling Coordinator's Operating Reserve obligation in each Zone shall be pro rata based upon the same proportion as the ratio of the product of its percentage obligation based on metered output and the sum of its metered Demand and firm exports bears to the total of such products for all Scheduling Coordinators in the Zone. The Scheduling Coordinator's percentage obligation based on metered output shall be calculated as the sum of 5% of its real-time Demand (except the Demand covered by firm purchases from outside the ISO Control Area) met by Generation from hydroelectric resources plus 7% of its Demand (except the Demand covered by firm purchases from outside the ISO Control Area) met by Generation from non-hydroelectric resources in that Zone, plus 100% of any Interruptible Imports and on-demand obligations which it schedules. Each Scheduling Coordinator's

Replacement Reserve obligation in each Zone is calculated as described in Section 8.12.3A. Scheduling Coordinator obligations for each Ancillary Service will be calculated based on the requirement for each Ancillary Service as the ISO determines prior to the adjustment set forth in Section 8.2.3.6.

8.6.2 Right to Self-Provide.

Each Scheduling Coordinator may choose to self-provide all, or a portion, of its Regulation, Operating Reserve, and Replacement Reserve obligation in each Zone. The ISO shall schedule self-provided Ancillary Services, Day-Ahead and Hour-Ahead, and Dispatch self-provided Ancillary Services in real time. To the extent that a Scheduling Coordinator self-provides, the ISO shall correspondingly reduce the quantity of the Ancillary Services concerned, which it procures as described in Sections 8.5.6 to 8.5.8A. In accordance with Section 34.8 and Section 8.10.2.2, if a Scheduling Coordinator uses capacity scheduled to self-provide Spinning Reserve, Non-Spinning Reserve, or Replacement Reserve to supply Uninstructed Imbalance Energy to the ISO from a Generating Unit, Curtailable Demand, or System Resource under circumstances that would cause the elimination of payments to the Scheduling Coordinator under Section 8.10.2.2 if the capacity had been bid and was selected by the ISO to supply the Ancillary Service, the Scheduling Coordinator shall pay to the ISO the amount of the payment that would be eliminated under that section. Scheduling Coordinators may trade Ancillary Services obligations so that any Scheduling Coordinator may reduce its Ancillary Services obligation through purchase of Ancillary Services capacity from another Scheduling Coordinator, or self-provide in excess of its obligation to sell Ancillary Services to another Scheduling Coordinator, subject to the limits specified under Section 8.6.4.2. If a Scheduling Coordinator's Day-Ahead self-provided Ancillary Service Schedule is decreased in the Hour-Ahead Market, such decrease shall be deemed to be replaced at the Market Clearing Price in the Hour-Ahead Market, pursuant to Section 8.7.

8.6.3 Services Which May Be Self-Provided.

The ISO shall permit Scheduling Coordinators to self-provide the following Ancillary Services:

- (a) Regulation;
- (b) Spinning Reserve;

- (c) Non-Spinning Reserve; and
- (d) Replacement Reserve.

The ISO may from time to time add other Ancillary Services to this list as it considers appropriate.

8.6.4 Time Frame for Informing ISO of Self-Provision.

8.6.4.1 Day-Ahead Schedule.

At the Day-Ahead scheduling process, Scheduling Coordinators shall be required to submit information on self-provided Ancillary Services within the time frame stated in Section 8.5.2.1. Failure to submit the required information within the stated time frame for any hour shall lead to the self-provision for that hour being declared invalid by the ISO, and under such circumstances the ISO shall purchase sufficient Ancillary Services to meet the Scheduling Coordinator's requirements to match its Day-Ahead Schedule.

8.6.4.2 Hour-Ahead Schedule.

Increases in each Scheduling Coordinator's self-provided Ancillary Service between the Day-Ahead and Hour-Ahead Markets shall be limited to the estimated incremental Ancillary Service requirement associated with the increase between the Day-Ahead and Hour-Ahead Markets in that Scheduling Coordinator's scheduled Zonal Demand. Notwithstanding this limit on increases in Hour-Ahead self-provision, a Scheduling Coordinator may buy or sell Ancillary Services through Inter-Scheduling Coordinator Ancillary Service Trades in the Hour-Ahead Market. In the Hour-Ahead scheduling process, Scheduling Coordinators shall be required to submit information on self-provided Ancillary Services within the time frame stated in Section 8.5.2.2. Failure to submit the required adjusted information within the stated time frame shall lead to the self-provision being declared invalid by the ISO, and under such circumstances the ISO shall purchase the additional Ancillary Services necessary to meet the requirements for that Scheduling Coordinator.

8.6.4.2A Information To Be Submitted By Scheduling Coordinators For Each Service.

Scheduling Coordinators electing to self-provide Ancillary Services shall submit the information for each self-provided Ancillary Service as described in Sections 8.5.6 to 8.5.8A, excluding the capacity price

information, but including the name of the trading Scheduling Coordinator in the case of Inter-Scheduling Coordinator Ancillary Service Trades.

In the event of an Inter-Scheduling Coordinator Ancillary Service Trade, the Scheduling Coordinators who are parties to that trade must agree on a Zone in which the trade is deemed to take place and notify the ISO accordingly. The Ancillary Service obligations in the Zone of each Scheduling Coordinator will be adjusted to reflect the trade. The Inter-Scheduling Coordinator Ancillary Service Trades section of a Schedule will include the following information for each Inter-Scheduling Coordinator Ancillary Service Trade.

- (a) Scheduling Coordinator's ID code;
- (b) Type of market (Day-Ahead or Hour-Ahead) and Trading Day;
- (c) Trading Scheduling Coordinator (buyer or seller);
- (d) Zone;
- (e) Schedule type-Regulation Up (ARGU), Regulation Down (ARGD), Spinning Reserve (ASPN), Non-Spinning Reserve (ANSP) or Replacement Reserve (AREP); and
- (f) Contracted MW amount of traded Ancillary Service obligation.

8.6.4.3 Acceptance of Self-Provided Ancillary Service Schedules.

The ISO will refuse to accept self-provided Ancillary Service Schedules only to the extent that they fail to meet requirements contained in this ISO Tariff. In particular, self-provided Ancillary Service Schedules must satisfy the following conditions:

- (a) the Scheduling Coordinator has a current certificate of technical eligibility for the Generating Units, System Units, Loads or System Resources selected for the Ancillary Services in question;
- (b) to the extent not provided under (a), the Generating Units, System Units, Loads and System Resources have the instrumentation, communication and metering equipment necessary to permit the ISO to dispatch the offered Ancillary Services and verify that the services have been provided;

- (c) the scheduling information provided by the Scheduling Coordinator is deemed to be valid in accordance with Appendix E and the ISO Protocols; and
- (d) the Generating Units, System Units, Loads or System Resources meet the ISO's locational requirements for the Ancillary Services.

8.7 Scheduling of Units to Provide Ancillary Services.

The ISO shall prepare supplier schedules for Ancillary Services (both self-provided and purchased by the ISO) for the Day-Ahead and the Hour-Ahead Markets. The ISO shall notify each Scheduling Coordinator no later than 1:00 p.m. of the day prior to the Trading Day of their Ancillary Services schedules for the Day-Ahead and no later than one hour prior to the operating hour of their Ancillary Services schedules for the Hour-Ahead. Where long-term contracts are involved, the information may be treated as standing information for the duration of the contract.

If, at any time after the issuance of Final Day-Ahead Schedules for the Trading Day and before the close of the Hour-Ahead Market for the first Settlement Period of the Trading Day, the ISO determines that it requires Ancillary Services in addition to those included in the Final Day-Ahead Schedule (in the appropriate Zone if procuring zonally), the ISO may procure such additional Ancillary Services by providing Scheduling Coordinators with amended supplier schedules for the Day-Ahead Markets that include Ancillary Services for which previously submitted (but not selected) bids remain available and have not previously been withdrawn. The ISO shall select such Ancillary Services in price merit order (and in the relevant Zone if the ISO is procuring Ancillary Services on a Zonal basis). Such amended supplier schedules shall be provided to the Scheduling Coordinators no later than the close of the Hour-Ahead Market for the first Settlement Period of the Trading Day.

Once the ISO has given Scheduling Coordinators notice of the Day-Ahead and Hour-Ahead Schedules, these schedules represent binding commitments made in the markets between the ISO and the Scheduling Coordinators concerned, subject to any amendments issued as described above. Any minimum energy input and output associated with Regulation and Spinning Reserve services shall be the responsibility of the Scheduling Coordinator, or provided in accordance with the must-offer obligation as

set forth in Section 40.7, as the ISO's auction does not compensate the Scheduling Coordinator for the minimum energy output of Generating Units or System Units, if any, bidding to provide these services. Accordingly, except as set forth under Section 40.7, the Scheduling Coordinators shall adjust their schedules to accommodate the minimum outputs required by the Generating Units or System Units, if any, to facilitate delivery of Energy from Ancillary Services.

Notwithstanding the foregoing, a Scheduling Coordinator who has sold or self-provided Regulation, Spinning Reserve, Non-Spinning Reserve or Replacement Reserve capacity to the ISO in the Day-Ahead Market shall be required to replace that capacity in whole or in part from the ISO if the scheduled self-provision is decreased between the Day-Ahead and Hour-Ahead Markets, or if the Ancillary Service associated with a Generating Unit, Curtailable Demand, or System Resource successfully bid in a Day-Ahead Ancillary Service Market is reduced in the Hour-Ahead Market, for any reason (other than the negligence or willful misconduct of the ISO, or a Scheduling Coordinator's involuntary decrease in such sold capacity or scheduled self-provision on the instruction of the ISO). The price for such replaced Ancillary Service shall be the Market Clearing Price in the Hour-Ahead Market for the Ancillary Service for the Settlement Period concerned for the Zone in which the Generating Units or other resources are located. The ISO will purchase the Ancillary Service concerned from another Scheduling Coordinator in the Hour-Ahead Market in accordance with the provisions of the ISO Tariff.

8.8 Black Start.

- (a) Black Start shall meet the standards specified for Black Start in this Tariff and Appendix K;
and
- (b) the ISO will Dispatch Black Start as required in accordance with the applicable Black Start agreement.

8.9 [Not Used]

8.10 Verification, Compliance Testing, and Audit of Ancillary Services.

Availability of both contracted and self-provided Ancillary Services shall be verified by the ISO by unannounced testing of Generating Units, Loads and System Resources, by auditing of response to ISO

Dispatch instructions, and by analysis of the appropriate Meter Data, or interchange schedules. The ISO may test the capability of any Generating Unit, System Unit, System Resource, external import of a System Resource, Load providing Curtailable Demand, or reactive device providing ancillary services. Participating Generators, owners or operators of Loads, operators of System Units or System Resources, owners or operators of reactive devices and Scheduling Coordinators shall notify the ISO immediately whenever they become aware that an Ancillary Service is not available in any way. All Participating Generators, owners or operators of Loads, operators of System Units or System Resources and owners or operators of reactive devices shall check, monitor and/or test their system and related equipment routinely to assure availability of the committed Ancillary Services. These requirements apply whether the Ancillary Services are contracted or self-provided. For a duration specified by the ISO, the ISO may suspend the technical eligibility certificate of a Scheduling Coordinator for a Generating Unit, System Unit, Load or System Resource, which repeatedly fails to perform. The ISO shall develop measures to discourage repeated non-performance on the part of both bidders and self-providers.

8.10A Compliance Testing for Regulation. The ISO may test the capability of any Generating Unit or System Resource providing Regulation by using the ISO EMS to move that Generating Unit's or System Resource's output over the full range of its Regulation capacity within a ten-minute period.

8.10B [Not Used]

8.10C Compliance Testing for Non-Spinning Reserve.

(a) Compliance Testing of a Generating Unit, System Unit or System Resource. The ISO may test the Non-Spinning Reserve capability of a Generating Unit, System Unit or an external import of a System Resource by issuing unannounced Dispatch instructions requiring the Generating Unit or System Unit to come on line and ramp up or, in the case of a System Resource, to affirmatively respond to real-time interchange schedule adjustment; all in accordance with the Scheduling Coordinator's bid. Such tests may not necessarily occur on the hour. The ISO shall measure the response of the Generating

Unit, System Unit or external import of a System Resource to determine compliance with its stated capabilities.

- (b) Compliance Testing of Curtailable Demand. The ISO may test the Non-Spinning Reserve capability of a Load providing Curtailable Demand by issuing unannounced Dispatch instructions requiring the operator of the Load to report the switchable Demand of that Load actually being served by the operator at the time of the instruction. No Load will be disconnected as part of the test.

8.10D Compliance Testing for Replacement Reserve.

- (a) Compliance Testing of a Generating Unit, System Unit or System Resource. The ISO may test the Replacement Reserve capability of a Generating Unit, System Unit or an external import of a System Resource by issuing unannounced Dispatch instructions requiring the Generating Unit or System Unit to come on line and ramp up or, in the case of a System Resource, to affirmatively respond to a real-time interchange schedule adjustment; all in accordance with the Scheduling Coordinator's bid. Such tests may not necessarily occur on the hour. The ISO shall measure the response of the Generating Unit, System Unit or external import of a System Resource to determine compliance with its stated capabilities.
- (b) Compliance Testing of a Curtailable Demand. The ISO may test the Replacement Reserve capability of a Load providing Curtailable Demand by issuing unannounced Dispatch instructions requiring the operator of the Load to report the switchable Demand of that Load actually being served by the operator at the time of the instruction. No Load will be disconnected as part of a test.

8.10E Compliance Testing for Voltage Support.

- (a) Compliance Testing of a Generating Unit. The ISO may test the Voltage Support capability of a Generating Unit by issuing unannounced Dispatch instructions requiring

the Generating Unit to adjust its power factor outside the specified power factor band of 0.90 lag to 0.95 lead, but within the limits of the Generating Unit capability curve.

- (b) Compliance Testing of Other Reactive Devices. The ISO may test the Voltage Support capability of other reactive devices (shunt capacitors, static var compensators, synchronous condensers) by issuing unannounced Dispatch instructions requiring operation of such devices.

8.10F Compliance Testing for Black Start. The ISO may test the Black Start capability of a Generating Unit by unannounced tests, which may include issuing Dispatch instructions to start and synchronize the resource, testing of all communications circuits, simulating switching needed to connect the Black Start Generating Unit to the transmission system, and testing the features unique to each facility that relate to Black Start service.

8.10F.1 Consequences of Failure to Pass Compliance Testing.

- (a) Notification of Compliance Testing Results. If a Generating Unit, Load, or System Resource fails a compliance test, the ISO shall notify the Scheduling Coordinator whose resource was the subject of the test and the Ancillary Service Provider or owner or operator of a System Resource providing Ancillary Services of such failure by any means as soon as reasonably practicable after the completion of the test. In addition, regardless of the outcome of the test, the ISO shall provide the Scheduling Coordinator whose resource was subject to a compliance test written notice of the results of such test. The ISO shall at the same time send a copy of the notice to the Ancillary Service Provider or owner or operator of a System Resource providing Ancillary Services.
- (b) Penalties for Failure to Pass Compliance Testing. The Scheduling Coordinator whose resource fails a compliance test shall be subject to the financial penalties provided for in the ISO Tariff. In addition, the ISO shall institute the sanctions described in Section 8.10N.

8.10G Performance Audits for Standard Compliance. In addition to testing under Section 8.10.1, the ISO will periodically audit the performance of resources providing Ancillary Services to confirm the ability of such resources to meet the applicable Ancillary Service standard for performance and control.

8.10G.1 Performance Audit for Regulation. The ISO will audit the performance of a Generating Unit providing Regulation by monitoring its response to ISO EMS control or, in the case of an external import of a System Resource providing Regulation, by monitoring the dynamic interchange response to ISO EMS control around its Set Point within its rated MW/minute capability over the range of Regulation capacity scheduled for the current Settlement Period.

8.10H Performance Audit for Spinning Reserve. The ISO will audit the performance of a Generating Unit or external import of a System Resource providing Spinning Reserve by auditing its response to Dispatch instructions and by analysis of Meter Data associated with the Generating Unit. Such audits may not necessarily occur on the hour. A Generating Unit providing Spinning Reserve shall be evaluated on its ability to respond to a Dispatch instruction, move at the MW/minute capability stated in its bid, reach the amount of Spinning Reserve capacity scheduled for the current Settlement Period within ten minutes of issue of the Dispatch instruction by the ISO, and respond to system frequency deviations outside the allowed frequency deadband. An external import of a System Resource providing Spinning Reserve shall be evaluated on its ability to respond to a Dispatch instruction, move at the MW/minute capability stated in its bid, reach the amount of Spinning Reserve capacity scheduled for the current Settlement Period within ten minutes of issue of the Dispatch instruction by the ISO.

8.10I Performance Audit for Non-Spinning Reserve. The ISO will audit the performance of a Generating Unit, Load, or System Resource providing Non-Spinning Reserve by auditing its response to Dispatch instructions, and by analysis of Meter Data associated with the resource. Such audits may not necessarily occur on the hour. A Generating Unit providing Non-Spinning Reserve shall be evaluated on its ability to respond to a Dispatch instruction, move in accordance with the time delay and MW/minute capability stated in its bid, and reach the amount of Non-Spinning Reserve capacity under the control of the ISO scheduled for the current Settlement Period within ten minutes of issue of the Dispatch instruction

by the ISO. An external import of a System Resource providing Non-Spinning Reserve shall be evaluated on its ability to respond to a Dispatch instruction, move in accordance with the time delay and MW/minute capability stated in its bid, and reach the amount of Non-Spinning Reserve capacity scheduled for the current Settlement Period within ten minutes of issue of the Dispatch instruction by the ISO. A Load providing Non-Spinning Reserve from Curtailable Demand shall be evaluated on its ability to respond to a Dispatch instruction, move in accordance with the time delay and MW/minute capability stated in its bid, and reach the amount of Non-Spinning Reserve capacity scheduled for the current Settlement Period within ten minutes of issue of the Dispatch instruction by the ISO.

8.10J Performance Audit for Replacement Reserve. The ISO will audit the performance of a Generating Unit, Load, or System Resource providing Replacement Reserve by auditing its response to Dispatch instructions, and by analysis of Meter Data associated with the resource. Such audits may not necessarily occur on the hour. A Generating Unit providing Replacement Reserve shall be evaluated on its ability to respond to a Dispatch instruction, start within the designated time delay, move at the MW/minute capability stated in its bid, reach the amount of Replacement Reserve capacity scheduled for the Settlement Period concerned within sixty minutes of issue of the Dispatch instruction, and sustain operation at this level for a sufficient time to assure availability over the specified period. An external import of a System Resource providing Replacement Reserve shall be evaluated on its ability to respond to a Dispatch instruction, start within the designated time delay, move at the MW/minute capability stated in its bid, reach the amount of Replacement Reserve capacity scheduled for the Settlement Period concerned within sixty minutes of issue of the Dispatch instruction, and sustain operation at this level for a sufficient time to assure availability over the specified period. A Load providing Replacement Reserve from Curtailable Demand shall be evaluated on its ability to respond to a Dispatch instruction, start within the designated time delay, move at the MW/minute capability stated in its bid, reach the amount of Replacement Reserve capacity scheduled for the Settlement Period concerned within sixty minutes of issue of the Dispatch instruction, and sustain operation at this level for a sufficient time to assure availability over the specified period.

8.10K Performance Audit for Voltage Support. The ISO will audit the performance of a resource providing Voltage Support by auditing of its response to Dispatch instructions, and by analysis of Meter Data associated with the resource. A resource providing Voltage Support shall be evaluated on its ability to provide reactive support over the stated power factor range of the resource, provide reactive support within the prescribed time periods, and demonstrate the effective function of automatic voltage control equipment for the amount of Voltage Support under the control of the ISO for the current Settlement Period.

8.10L Performance Audit for Black Start. The ISO will audit the performance of a Black Start Generating Unit by analysis of Meter Data and other records to determine that the performance criteria relating to the Black Start from that Black Start Generating Unit were met when required.

8.10M Consequences of Failure to Pass Performance Audits.

- (a) Notification of Performance Audit Results. The ISO shall give the Scheduling Coordinator for an Ancillary Service Provider whose resource was subject to a performance audit written notice of the results of such audit. The ISO will at the same time send a copy of the notice to the Ancillary Service Provider.
- (b) Penalties for Failure to Pass Performance Audit. The Scheduling Coordinator for an Ancillary Service Provider whose resource fails a performance audit shall be subject to the financial penalties provided for in the ISO Tariff. In addition the sanctions described in Section 8.10 shall come into effect.

8.10N Sanctions for Poor Performance.

8.10N.1 Warning Notice. If an Ancillary Service resource fails a compliance test or a performance audit, the ISO will issue a warning notice to the Scheduling Coordinator for that resource and at the same time will send a copy of the notice to the owner and operator of the resource.

8.10N.2 Scheduling Coordinator's Option to Test. On receipt of a warning notice the Ancillary Service Provider for the resource concerned may request the ISO, through its Scheduling Coordinator, to test the capability of the Ancillary Service resource concerned. The ISO shall carry out such test as soon

as practicable and the cost of such test shall be paid by the Scheduling Coordinator irrespective of the result of the test.

8.10N.3 Duration of Warning Notice. A warning notice shall continue in effect until:

- (a) the Ancillary Service resource is next tested by the ISO whether such a test is called for by the Scheduling Coordinator under Section 8.10N.2 or carried out by the ISO under Section 8.10; or
- (b) the expiration of a period of six calendar months from the date upon which the ISO notified the Scheduling Coordinator that the Ancillary Service resource failed the test or the performance audit which gave rise to the issue of the warning notice, whichever is the earlier.

8.10P Second failure. An Ancillary Service resource which fails a compliance test or a performance audit conducted during the period when a warning notice for that resource is in effect shall be disqualified immediately from providing the Ancillary Service concerned whether as part of the ISO's auction or as part of a self-provision arrangement, and shall not be permitted to submit a bid to the ISO or be part of a self-provision arrangement until such time as it has successfully re-passed the approval and certification procedure described in the relevant Part of Appendix K.

8.10.1 Periodic Testing of Units.

The ISO shall periodically conduct unannounced tests of resources providing Ancillary Services to confirm the ability of such resources to meet the applicable Ancillary Service standard for performance and control. The ISO may test Generating Units, System Units, Loads and System Resources in the manner described herein. The frequency of testing shall be within such timeframes as are reasonable under all the circumstances. Scheduling Coordinators shall manage the resulting Energy output if notification of testing permits the Energy to be scheduled. If a Generating Unit, System Unit, Load, or System Resource fails to meet requirements in a test under this section, the ISO shall notify the relevant Participating Generator, owner or operator of Loads, System Units or System Resources, or Scheduling

Coordinator of such failure as soon as reasonably practicable after the completion of the test. Failure to meet requirements shall lead to the penalties described in Section 2.5.26.

8.10.1.1 Regulation. The ISO shall continuously monitor the response of a Generating Unit, System Unit, or System Resource to the ISO's Regulation instructions in order to determine compliance with Dispatch instructions.

8.10.1.2 Spinning Reserve. The ISO shall test the Spinning Reserve capability of a Generating Unit, System Unit or System Resource by issuing unannounced Dispatch instructions requiring the Generating Unit, System Unit or System Resource to ramp up to its ten minute capability. The ISO shall measure the response of the Generating Unit, System Unit or System Resource to determine compliance with requirements. Such tests may not necessarily occur on the hour. The Scheduling Coordinator for the Generating Unit, System Unit or System Resource shall be paid the Energy Bid price of the Generating Unit or System Unit for the output under the Spinning Reserve test.

8.10.1.3 Non-Spinning Reserve. The ISO may test the Non-Spinning Reserve capability of a Generating Unit, Load, System Unit or System Resource by issuing unannounced Dispatch instructions requiring the Generating Unit, Load, System Unit or System Resource to come on line and ramp up or to reduce Demand to its ten minute capability. The ISO shall measure the response of the Generating Unit, System Unit, System Resource or Load to determine compliance with requirements. The Scheduling Coordinator for the Generating Unit, System Unit, Load or System Resource shall be paid the Energy (or Demand reduction) Bid price of the Generating Unit, System Unit, Load or System Resource for its output or reduction, under the Non-Spinning Reserve test.

8.10.1.4 Replacement Reserve. The ISO may test the Replacement Reserve capability of a Generating Unit, Load, System Unit or System Resource by issuing unannounced Dispatch instructions requiring the Generating Unit, Load, System Unit or System Resource to come on line and ramp up or reduce Demand to its sixty minute capability. The ISO shall measure the response of the Generating Unit, Load, System Unit or System Resource to determine compliance with requirements. The Scheduling Coordinator for the Generating Unit, Load, System Unit or System Resource shall be paid the Energy or

Demand reduction Bid price of the Generating Unit, Load, System Unit or System Resource for the output, or reduction, of the Generating Unit, Load, System Unit or System Resource under the Replacement Reserve test.

8.10.1.5 Voltage Support. The ISO shall monitor a Generating Unit's response to Voltage Support instructions in order to determine compliance with Dispatch instructions.

8.10.1.6 Black Start. The ISO may test the Black Start capability of a Generating Unit by issuing unannounced dispatch instructions requiring the Generating Unit to start on a Black Start basis. The ISO shall measure the response of the Generating Unit to determine compliance with the terms of the Black Start contract. The Scheduling Coordinator or Black Start Generator as stated in Section 8.11.5 for the Generating Unit shall be paid the Generating Unit's contract price for the output under the Black Start test.

8.10.2 Penalties for Failure to Pass Tests and Rescission of Payment for Non-Delivery.

8.10.2.1 Penalties for Failure to Pass Tests.

A Generating Unit, Curtailable Demand, System Unit or System Resource that fails an availability test, as determined under criteria to be established by the ISO, shall be deemed not to have been available to provide the Ancillary Service concerned or the relevant portion of that Service for the entire period the Generating Unit, Curtailable Demand, System Unit or System Resource was committed to provide the Service, unless appropriate documentation (i.e., daily test records) confirming the availability of that service during the committed period(s) is presented to the ISO. The "committed period" is defined as the total of all the hours/days the Generating Unit, Curtailable Demand, System Unit or System Resource was scheduled by the ISO to provide the Ancillary Service beginning from: (i) the last successful availability test; or (ii) the last time the Generating Unit, Curtailable Demand, System Unit or System Resource actually provided Energy or reduced Demand as part of the Ancillary Service; whichever results in a shorter committed period. The Scheduling Coordinator for a Generating Unit, Curtailable Demand, System Unit or System Resource that fails an availability test shall not be entitled to payment for the Ancillary Service concerned for the committed period and adjustments to reflect this shall be made in the calculation of payments to the Scheduling Coordinator, provided that any such penalty shall be reduced

to reflect any adjustment made over the duration of the committed period under Section 8.10.2.2 or 8.10.2.3.

System Units engaged in self-provision of Ancillary Services, or providing Ancillary Services to the ISO are subject to the same testing, compensation, and penalties as are applied to individual Generating Units engaged in self-provision or provision of Ancillary Services. To perform testing, the ISO will bias the MSS's MSRE to test the responsiveness of the System Unit.

If payments for capacity for a particular Ancillary Service in a particular Settlement Period would be rescinded under more than one provision of this Section 8.10.2, the total amount to be rescinded for a particular Ancillary Service in a particular Settlement Period shall not exceed the total payment due in that Settlement Period.

8.10.2.2 Rescission of Payments for Unavailability.

If capacity scheduled into the ISO's Ancillary Services markets from a Generating Unit, Curtailable Demand, System Unit or System Resource is unavailable during the relevant Settlement Interval, then payments will be rescinded as described herein. For self-provided Ancillary Services, the payment obligation shall be equivalent to that which would arise if the Ancillary Services had been bid into each market in which they were scheduled.

8.10.2.2.1 If the ISO determines that a Scheduling Coordinator has supplied Uninstructed Imbalance Energy to the ISO during a Settlement Interval from the capacity of a Generating Unit, System Unit or System Resource that is obligated to supply Spinning Reserve, Non-Spinning Reserve, or Replacement Reserve to the ISO during such Settlement Interval, payments to the Scheduling Coordinator representing the Generating Unit, System Unit or System Resource for the Ancillary Service capacity used to supply Uninstructed Imbalance Energy shall be eliminated to the extent of the deficiency, except to the extent (i) the deficiency in the availability of Ancillary Service capacity from the Generating Unit, System Unit or System Resource is attributable to control exercised by the ISO in that Settlement Interval through AGC operation, an RMR Dispatch Notice, or dispatch to avoid an intervention in Market

operations or to prevent a System Emergency; or (ii) a penalty is imposed under Section 8.10.2.1 with respect to the deficiency.

8.10.2.2.2 If a Curtailable Demand is insufficient to deliver the full amount of the Non-Spinning and Replacement Reserve to which that Curtailable Demand is obligated in that Settlement Interval, then the related capacity payments will be rescinded to the extent of that deficiency as explained in Section 8.10.2.2.4 and 8.10.2.2.5, unless a penalty is imposed on that Curtailable Demand for that Settlement Interval under Section 8.10.2.1.

8.10.2.2.3 The ISO shall calculate the real-time ability of each Generating Unit and System Unit to deliver Energy from Ancillary Services capacity awarded or self-provided for each Settlement Interval based on its operational ramp rate as described in Section 30.4.6, maximum operating capability, and actual telemetered output. If the Generating Unit or System Unit cannot deliver the full amount of Energy from the awarded or self-provided Spinning, Non-Spinning or Replacement Reserve for a Settlement Interval then Ancillary Services capacity payments for the amount of Energy that cannot be delivered for the particular Settlement Interval shall be rescinded.

8.10.2.2.4 This Section 8.10.2.2.4 shall not apply to the capacity payment for any particular Ancillary Service if the Zonal Market Clearing Price determined in accordance with Sections 8.5.7, 8.5.8 or 8.5.8A is less than or equal to zero. For those Ancillary Services for which such Zonal Market Clearing Prices are greater than zero, the payment for Ancillary Service capacity otherwise payable under Section 8.11.2, 8.11.3, and/or 8.11.3A shall be reduced by one sixth of the product of the applicable prices and the amount of Ancillary Service capacity from which the Generating Unit, Curtailable Demand, System Unit or System Resource has supplied Uninstructed Imbalance Energy in a Settlement Interval. If a Scheduling Coordinator schedules Ancillary Services through both the Day-Ahead and Hour-Ahead Markets, capacity payments due the Scheduling Coordinator from each market will be rescinded in proportion to the amount of capacity sold to the ISO in each market.

8.10.2.2.5 Payment shall be eliminated first for any Replacement Reserve capacity for which the Generating Unit, Curtailable Demand, System Unit or System Resource would otherwise be entitled to

payment. If the amount of Ancillary Service capacity from which the Generating Unit, System Unit or System Resource has supplied Uninstructed Imbalance Energy exceeds the amount of Replacement Reserve capacity for which it would otherwise be entitled to receive payment, payment shall be eliminated for Non-Spinning Reserve capacity, and then for Spinning Reserve capacity, until payment has been withheld for the full amount of Ancillary Service capacity from which the Generating Unit, Curtailable Demand, System Unit or System Resource supplied Uninstructed Imbalance Energy.

8.10.2.2.6 For each Settlement Interval in which a Generating Unit, Curtailable Demand, System Unit or System Resource fails to actually supply Energy from Spinning Reserve, Non-Spinning Reserve or Replacement Reserve capacity in accordance with a Dispatch Instruction, or supplies only a portion of the Energy specified in the Dispatch Instruction, the capacity payment will be pro-rated to reflect the unavailability in that Settlement Interval of the difference between (1) the total MW of the particular Ancillary Service scheduled in that Settlement Period and (2) the amount of Energy, if any, supplied in response to the Dispatch Instruction in that Settlement Interval.

8.10.2.3 Rescission of Payments When Dispatch Instruction is Not Followed.

If the total metered output of a Generating Unit, Curtailable Demand, System Unit or System Resource is insufficient to supply the amount of Instructed Imbalance Energy associated with a Dispatch Instruction issued in accordance with a bid on Spinning Reserve, Non-Spinning Reserve, or Replacement Reserve in any Settlement Interval, then the capacity payment associated with the difference between the total scheduled amount of each Ancillary Service for which Insufficient Energy was delivered, and the actual output attributed to the response to the Dispatch Instruction on each Ancillary Service, shall be rescinded. However, no capacity payment shall be rescinded if the shortfall in the metered output of the Generating Unit, Curtailable Demand, System Unit, or System Resource is less than a deadband amount published by ISO on the ISO Home Page at least twenty-four hours prior to the Settlement Interval. For any Settlement Interval with respect to which no deadband amount has been published by the ISO, the deadband amount shall be zero MWH. If the Generating Unit, Curtailable Demand, System Unit or System Resource is scheduled to provide more than one Ancillary Service in the Settlement Period, then the actual output will be attributed first to Replacement Reserve, then to Non-Spinning Reserve, and

finally to Spinning Reserve, and the capacity payments associated with the balance of each Ancillary Service shall be rescinded. If the same Ancillary Service is scheduled in both the Day-Ahead and Hour-Ahead Markets, then payments shall be rescinded in proportion to the amount of each Ancillary Service scheduled in each market.

8.10.2.4 Penalties applied pursuant to Section 8.10.2.1, and payments rescinded pursuant to Section 8.10.2.2 and 8.10.2.3 shall be redistributed to Scheduling Coordinators in proportion to ISO Control Area metered Demand and scheduled exports for the same Trading Day.

8.10.2.5 If the ISO determines that non-compliance of a Load, Generating Unit, System Unit or System Resource, with an operating order or Dispatch Instruction from the ISO, or with any other applicable technical standard under the ISO Tariff, causes or exacerbates system conditions for which the WECC imposes a penalty on the ISO, then the Scheduling Coordinator of such Load, Generating Unit, System Unit or System Resource shall be assigned that portion of the WECC penalty which the ISO reasonably determines is attributable to such non-compliance, in addition to any other penalties or sanctions applicable under the ISO Tariff.

8.10.2.6 Temporary Exemption from Rescission of Energy Payments.

Any Participating Load that has entered into a Participating Load Agreement and has responded to a Dispatch Instruction will be exempt from the requirements of Section 8.10.2.2.3 in the hour of the Dispatch and for the following two (2) hours during the period beginning on June 15, 2000 and ending on the date specified in a notice ("Notice Terminating Temporary Exemption") to be issued by the ISO. Such notice shall be posted on the ISO Home Page and distributed to Market Participants via e-mail at least seven (7) calendar days in advance of the termination of this temporary exemption.

8.11 Settlements For Contracted Ancillary Services.

Based on the prices and quantities determined in accordance with this Section, the ISO shall operate a daily Settlement function for Ancillary Services it contracts for with Scheduling Coordinators.

The ISO shall calculate imbalances between scheduled, instructed and actual quantities of Energy provided based upon Meter Data obtained pursuant to Section 10. Schedules between Control

Areas shall be deemed as being delivered in accordance with Good Utility Practice. Dynamic schedules shall be integrated over time through the operating hour and the MWh quantity obtained by such integration shall be deemed to be the associated scheduled interchange for that operating hour. The difference between actual and scheduled interchange shall then be addressed in accordance with the WECC and NERC inadvertent interchange practices and procedures. Following this practice, all dynamic schedules for Ancillary Services provided to the ISO from System Resources in other Control Areas shall be deemed delivered to the ISO. The difference between the Energy requested by the ISO and that actually delivered by the other Control Area shall then be accounted for and addressed through the WECC and NERC inadvertent interchange practices and procedures.

Separate payments shall be calculated for each Settlement Period t for each Generating Unit, System Unit, System Resource and Curtailable Demand. The ISO shall then calculate a total daily payment for each Scheduling Coordinator for all the Generating Units, System Units, System Resources and Curtailable Demands that it represents for each Settlement Period t .

The settlements for the Hour-Ahead Markets shall be calculated by substituting Hour-Ahead prices in the relevant formulae and deducting any amounts due to the ISO from Scheduling Coordinators who buy back in the Hour-Ahead Market Regulation, Spinning Reserve, Non-Spinning Reserve or Replacement Reserve capacity they sold to the ISO in the Day-Ahead Market.

8.11.1 Regulation.

Regulation Up and Regulation Down payments shall be calculated separately.

Quantities. The following quantity definitions shall be used for each Scheduling Coordinator in the settlement process:

$AGCU_{pQDA_{xt}}$ = the Scheduling Coordinator's total quantity of Regulation Up capacity in Zone X sold through the ISO auction and scheduled Day-Ahead j for Settlement Period t .

$AGCDown_{QDA_{xt}}$ = the Scheduling Coordinator's total quantity of Regulation Down capacity in Zone X sold through the ISO auction and scheduled Day-Ahead j for Settlement Period t .

$EnQInst_{xt}$ = Instructed Imbalance Energy increase or decrease in Zone X in real-time Dispatch for each Dispatch Interval b of Settlement Period t, determined in accordance with the ISO Protocols.

Prices. The prices in the Settlement process for Regulation Up and Regulation Down shall be those determined in Section 8.5.6.

Adjustment: penalty described in Section 8.10.2.1.

$PAGCUpDA_{xt}$ = the Market Clearing Price, PAGC, in Zone X for Regulation Up capacity in the Day-Ahead Market for Settlement Period t.

$PAGCDownDA_{xt}$ = the Market Clearing Price, PAGC, in Zone X for Regulation Down capacity in the Day-Ahead Market for Settlement Period t.

Payments. Scheduling Coordinators for Generating Units providing Regulation Up capacity through the ISO auction shall receive the following payments for Regulation Up:

$$AGCUpPay_{xt} = AGCUpQDA_{xt} * PAGCUpDA_{xt} - Adjustment$$

Scheduling Coordinators for Generating Units providing Regulation Down capacity through the ISO auction shall receive the following payments for Regulation Down:

$$AGCDownPay_{xt} = AGCDownQDA_{xt} * PAGCDownDA_{xt} - Adjustment$$

Scheduling Coordinators for Generating Units shall receive the following payment for Energy output from Regulation in accordance with the settlement for Instructed Imbalance Energy under Section 11.2.4.1:

$REPA_{ixt}$ = the Regulation Energy Payment Adjustment for Generating Unit i in Zone X for

$$\sum_i [(EnQInst_{ixt} * Zonal Settlement Interval ExPost Price in Zone X) + REPA_{ixt}]$$

Settlement Period t calculated as follows:

$$[(R_{UPixt} * C_{UP}) + (R_{DNixt} * C_{DN})] * \max (\$20/MWh, P_{xt})$$

Where

R_{UPixt} = the upward range of generating capacity for the provision of Regulation from Generating Unit i in Zone X included in the bid accepted by the ISO for Generating Unit i for Settlement Period t , weighted in proportion to the ISO's need for upward Regulation. The weighting factors will be specified within a range from 0-100 percent. The weighting factors will be set at the discretion of the ISO based on system conditions, and will be set at a level that will provide sufficient incentive to the market to supply upward Regulation for the ISO's purposes of satisfying WECC criteria and NERC control performance standards. The ISO shall post the weighting factors consistent with the ISO Weighting Procedure, posted on the ISO website.

R_{DNixt} = the downward range of generating capacity for the provision of Regulation for Generating Unit i in Zone X included in the bid accepted by the ISO for Generating Unit i for Settlement Period t , weighted in proportion to the ISO's need for downward Regulation. The weighting factors will be specified within a range from 0-100 percent. The weighting factors will be set at the discretion of the ISO based on system conditions, and will be set at a level that will provide sufficient incentive to the market to supply downward Regulation for the ISO's purposes of satisfying WECC criteria and NERC control performance standards. The ISO shall post the weighting factors consistent with the ISO Weighting Procedure, posted on the ISO website.

C_{UP} = 0 to 1

C_{DN} = 0 to 1

P_{xt} = the Hourly Ex Post Price for Zone X in Settlement Period t .

The ISO may modify the value of the constants C_{UP} or C_{DN} within a range of 0-1 either generally in regard to all hours or specifically in regard to particular times of the day, after the ISO Governing Board

approves such modification, by a notice issued by the Chief Executive Officer of the ISO and posted on the ISO Internet "Home Page," at <http://www.ISO.com>, or such other Internet address as the ISO may publish from time to time, specifying the date and time from which the modification shall take effect, which shall be not less than seven (7) days after the Notice is issued.

REPA shall not be payable unless the Generating Unit is available and capable of being controlled and monitored by the ISO Energy Management System over the full range of its Scheduled Regulation capacity for the entire Settlement Period at least the ramp rates (increase and decrease in MW/minute) stated in its bid. In addition, the total Energy available (R_{UP} plus R_{DN}) may be adjusted to be only R_{UP} or only R_{DN} , a percentage of R_{UP} or R_{DN} , or the sum of R_{UP} and R_{DN} , depending on the needs of the ISO for each direction of Regulation service.

8.11.2 Spinning Reserve.

Quantities. The following quantity definitions shall be used for each Scheduling Coordinator in the Settlement process:

$SpinQDA_{xt}$ = the Scheduling Coordinator's total quantity of Spinning Reserve capacity in Zone X sold through the ISO auction and scheduled Day-Ahead for Settlement Period t.

$EnQInst_{xt}$ = Instructed Imbalance Energy output in Zone X in real-time Dispatch for Settlement Period t, supplied in accordance with the ISO Protocols.

Prices. The prices in the Settlement process for Spinning Reserve shall be those determined in Section 8.5.7.

$Adjustment$ = penalty described in Section 8.10.2.1, or rescinded capacity payments described in Section 8.10.2.2 or 8.10.2.3.

$PspDA_{xt}$ = Market Clearing Price, Psp , in Zone X for Spinning Reserve capacity in the Day-Ahead Market for Settlement Period t.

Payments. Scheduling Coordinators for Generating Units, System Units, or System Resources providing Spinning Reserve capacity through the ISO auction shall receive the following payments for Spinning Reserve capacity:

$$SpinPay_{xt} = SpinQDA_{xt} * PspDA_{xt} - Adjustment$$

Scheduling Coordinators for Generating Units, System Units, or System Resources shall receive the following payments for Energy output from Spinning Reserve capacity:

$$EnQInst_{xt} * Resource-Specific Settlement Interval Ex Post Price_{xt}$$

8.11.3 Non-Spinning Reserve.

Quantities. The following quantity definitions shall be used for each Scheduling Coordinator in the Settlement process:

$NonSpinQDA_{xt}$ = the Scheduling Coordinator's total Quantity of Non-Spinning Reserve capacity in Zone X sold through the ISO's auction and scheduled Day-Ahead for Settlement Period t.

$EnQInst_{xt}$ = Instructed Imbalance Energy output or Demand reduction in Zone X in real-time Dispatch for Settlement Period t, supplied in accordance with the ISO Protocols.

Prices. The prices in the Settlement process for Non-Spinning Reserve shall be those determined in Section 8.5.8.

$Adjustment$ = penalty described in Section 8.10.2.1, or rescinded capacity payments described in Section 8.10.2.2 or 8.10.2.3.

$PnonspDA_{xt}$ = Market Clearing Price, $Pnonsp$, in Zone X for Non-Spinning Reserve capacity in the Day-Ahead Market for Settlement Period t.

Payments. Scheduling Coordinators for Generating Units, System Units, System Resources, or Loads supplying Non-Spinning Reserve capacity through the ISO auction shall be paid the following for the Non-Spinning Reserve capacity:

$$NonspPay_{xt} = NonSpinQDA_{xt} * PnonspDA_{xt} - Adjustment$$

Scheduling Coordinators for Generating Units, System Units, System Resources or Loads shall receive the following payments for Energy output from Non-Spinning Reserve capacity:

$$EnQInst_{xt} * Resource-Specific Settlement Interval Ex Post Price_{xt}$$

8.11.3A Replacement Reserve.

Quantities. The following quantity definitions shall be used for each Scheduling Coordinator in the Settlement process:

$RepResQDA_{xt}$ = the Scheduling Coordinator's total quantity of Replacement Reserve capacity in Zone X sold through the ISO auction scheduled Day-Ahead for Settlement Period t, and from which Energy has not been generated.

$EnQInst_{xt}$ = Instructed Imbalance Energy output or Demand reduction in Zone X in real-time Dispatch for Settlement Period t, supplied in accordance with the ISO Protocols.

Prices. The prices in the Settlement process for Replacement Reserve shall be those determined in Section 8.5.8A.

$Adjustment$ = penalty described in Section 8.10.2.1, or rescinded capacity payments described in Section 8.10.2.2 or 8.10.2.3.

$PRepResDA_{xt}$ = Market Clearing Price, PRepRes, in Zone X for Replacement Reserve capacity in the Day-Ahead Market for Settlement Period t.

Payments. Scheduling Coordinators for Generating Units, System Units, System Resources, or Loads providing Replacement Reserve capacity through the ISO auction shall receive the following payments for the portion of a Scheduling Coordinator's Replacement Reserve capacity from which Energy has not been generated:

$$RepResPay_{ijt} = (RepResQDA_{xt} -) * PRepResDA_{xt-Adjustment}$$

Scheduling Coordinators shall not receive capacity payments for the portion of a Scheduling Coordinator's Replacement Reserve capacity from which Energy has been generated. The payments for Energy output from Replacement Reserve capacity are calculated as follows:

$$EnQInst_{ijt} * Resource-Specific Settlement Interval Ex Post Price_{xt}$$

8.11.4 Voltage Support.

The total payments for each Scheduling Coordinator shall be the sum of the short-term procurement payments, based on opportunity cost, as described in Section 8.5.9, and the payments under long-term contracts.

8.11.5 Black Start.

Quantities. The following quantities shall be used in the Settlement process:

$EnQBS_{ijt}$ = Energy output from Black Start made by Generating Unit i from Scheduling Coordinator j (or Black Start Generator j, as the case may be) for Settlement Period t, pursuant to the ISO's order to produce.

Prices. The prices used in the Settlement process are those described in the contracts referred to in Section 8.5.10.

Adjustment = penalty described in Section 8.10.2.1.

Payments. Scheduling Coordinators for owners of Reliability Must-Run Units (or Black Start Generators, as the case may be) shall receive the following payments for Energy output from Black Start facilities:

$$BSEN_{ijt} = (EnQBS_{ijt} * EnBid_{ijt}) + BSSUP_{ijt-Adjustment}$$

where $BSSUP_{ijt}$ is the start-up payment for a Black Start successfully made by Generating Unit i of Scheduling Coordinator j (or Black Start Generator j) in Trading Interval t calculated in accordance with the applicable Reliability Must-Run Contract (or the Interim Black Start Agreement as the case may be).

8.12 Settlement for User Charges for Ancillary Services.

(a) The ISO shall determine a separate hourly user rate for Regulation, Spinning Reserve, Non-Spinning Reserve and Replacement Reserve for each Settlement Period purchased in the Day-Ahead Market, and in the Hour-Ahead Market. Each rate will be charged to Scheduling Coordinators on a volumetric basis applied to each Scheduling Coordinator's obligation for the Ancillary Service

concerned which it has not self-provided, as adjusted by any Inter-Scheduling Coordinator Ancillary Service Trades.

Each Scheduling Coordinator's obligation for Regulation, Spinning Reserve, Non-Spinning Reserve and Replacement Reserve for each Zone shall be calculated in accordance with Section 8.6.1, notwithstanding any adjustment to the quantities of each Ancillary Service purchased by the ISO in accordance with Section 8.2.3.6.

The cost of Voltage Support and Black Start shall be allocated to Scheduling Coordinators as described in Sections 8.12.4 and 8.12.5.

Quantities and rates for the Hour-Ahead Markets shall be calculated by substituting the Hour-Ahead quantities and prices in the relevant formulae (including self-provided quantities of the Ancillary Service) except that the user rates for Regulation, Spinning Reserve, Non-Spinning Reserve and Replacement Reserve capacity shall be calculated by dividing the net payments made by the ISO for each service by the MW quantity purchased for each service. The net payments are the total payments for each service net of sums payable by Scheduling Coordinators who have bought back in the Hour-Ahead Regulation, Spinning Reserve, Non-Spinning Reserve or Replacement Reserve capacity, as the case may be, which they had sold to the ISO in the Day-Ahead Market.

Ancillary Services obligations may be negative, and credits for such negative obligations will be in accordance with the rates calculated in Sections 8.12.1, 8.12.2, 8.12.3 and 8.12.3A, except that a Scheduling Coordinator's credit shall be reduced by the greater of: a) the amount of any self-provision scheduled from resources which are deemed to meet the ISO's Ancillary Services standards, and which are not subject to the certification and testing requirements of the ISO Tariff; or b) if the ISO has no incremental requirement to be met in the Hour-Ahead Market for an Ancillary Service, the incremental amount of such service scheduled by that Scheduling Coordinator in the Hour-Ahead Market.

The ISO will allocate the Ancillary Services capacity charges, for both Day-Ahead and Hour-Ahead Markets, on a Zonal basis if the Day-Ahead Ancillary Services market is procured on a Zonal basis. The ISO will allocate the Ancillary Services capacity charges, for both the Day-Ahead and Hour-

Ahead Markets, on an ISO Control Area wide basis if the Day-Ahead Ancillary Services market is defined on an ISO Control Area wide basis.

(b) If, in any Settlement Period, no quantity of Regulation, Spinning Reserve, Non-Spinning Reserve or Replacement Reserve is purchased in the Day-Ahead Market or the Hour-Ahead Market due to the operation of Section 8.2.3.6, then in lieu of the user rate determined in accordance with Section 8.12.1, 8.12.2, 8.12.3, or 8.12.3A, as applicable, the user rate for the affected Ancillary Service for that Settlement Period shall be determined as follows:

(i) If the affected market is a Day-Ahead Market, the user rate for the affected Ancillary Service shall be set at the lowest capacity reservation price for an unaccepted qualified capacity bid in the Day-Ahead Market for the same Settlement Period for that Ancillary Service or for another Ancillary Service that meets the requirements for the affected Ancillary Service. If there are no such unaccepted bids, the user rate for the affected Ancillary Service shall be the lowest Market Clearing Price for the same Settlement Period established in the Day-Ahead Market for another Ancillary Service that meets the requirements for the affected Ancillary Service.

(ii) If the affected market is an Hour-Ahead Market, the user rate for the affected Ancillary Service shall be set at the lowest capacity reservation price for an unaccepted qualified capacity bid in the Hour-Ahead Market for the same Settlement Period for that Ancillary Service or for another Ancillary Service that meets the requirements for the affected Ancillary Service. If there are no such unaccepted bids, the user rate for the affected Ancillary Service shall be the user rate for the same Ancillary Service in the Day-Ahead Market in the same Settlement Period.

(c) With respect to each Settlement Period, in addition to the user rates determined in accordance with Sections 8.12.1 through 8.12.3A or Section 8.12(b), as applicable, each Scheduling Coordinator shall be charged an additional amount equal to its proportionate share, based on total purchases by Scheduling Coordinators of Regulation, Spinning Reserve, Non-Spinning Reserve and Replacement Reserve of the amount, if any, by which (i) the total payments to Scheduling Coordinators pursuant to Section 8.11.1 through 8.11.3A, for the Day-Ahead Market and Hour-Ahead Market and all

Zones, exceed (ii) the total amounts charged to Scheduling Coordinators pursuant to Section 8.12.1 through 8.12.3A, for the Day-Ahead Market and Hour-Ahead Market and all Zones. If total amounts charged to Scheduling Coordinators exceed the total payments to Scheduling Coordinators, each Scheduling Coordinator will be refunded its proportionate share, based on total purchases by Scheduling Coordinators of Regulation, Spinning Reserve, Non-Spinning Reserve and Replacement Reserve.

8.12.1 Regulation.

Regulation Up and Regulation Down charges shall be calculated separately. The user rate per unit of purchased Regulation service for each Settlement Period in the Day-Ahead Market for each Zone shall be calculated by dividing the total Regulation capacity payments by the ISO's total MW purchases of Regulation for that Settlement Period for that Zone which has not been self-provided by Scheduling Coordinators. The ISO will calculate the user rate for Regulation Up in each Zone for each Settlement Period as:

$$RegRateUpDA (\$/MW) = AGCUpPayDA / AGCUpPurchDA$$

where:

$AGCUpPayDA$ = Total Regulation Up payments for the Settlement Period in the Day-Ahead Market for the Zone.

$AGCUpPurchDA$ = the total ISO Regulation Up MW purchases in the Day-Ahead Market for the Settlement Period for the Zone, excluding that which has been self-provided by Scheduling Coordinators.

The ISO will calculate the user rate for Regulation Down in each Zone for each Settlement Period as:

$$RegRateDownDA (\$/MW) = AGCDownPayDA / AGCDownPurchDA$$

where:

$AGCDownPayDA$ = Total Regulation Down payments for the Settlement Period in the Day-Ahead Market for the Zone.

AGCDownPurchDA = the total ISO Regulation Down MW purchases in the Day-Ahead Market for the Settlement Period for the Zone, excluding that which has been self-provided by Scheduling Coordinators.

For each Settlement Period, each Scheduling Coordinator shall pay to the ISO a sum calculated as follows for each Zone:

$$RegRateUpDA * AGCUpOblig$$

where *AGCUpOblig* is the Scheduling Coordinator's obligation for Regulation Up in the Zone in the Settlement Period for which it has not self-provided.

$$RegRateDownDA * AGCDownOblig$$

where *AGCDownOblig* is the Scheduling Coordinator's obligation for Regulation Down in the Zone in the Settlement Period for which it has not self-provided.

8.12.2 Spinning Reserve.

The user rate per unit of purchased Spinning Reserve for each Settlement Period in the Day-Ahead Market for each Zone shall be calculated by dividing the total capacity payments for Spinning Reserve by the ISO's total MW purchases of Spinning Reserve for that Settlement Period for that Zone which has not been self-provided by Scheduling Coordinators. The ISO will calculate the user rate for Spinning Reserve in each Zone for each Settlement Period as:

$$SpRateDA(\$ / MW) = \frac{SpinPayDA}{SpinPurchDA}$$

where:

SpinPayDA = Total Spinning Reserve payments for the Settlement Period in the Market for the Zone Day-Ahead.

SpinPurchDA = the total ISO Spinning Reserve MW purchases in the Day-Ahead Market for the Settlement Period for the Zone, excluding that which has been self-provided by Scheduling Coordinators.

For each Settlement Period, each Scheduling Coordinator shall pay to the ISO a sum calculated as follows for each Zone:

$$SPRateDA * SpinOblig$$

where *SpinOblig* is the Scheduling Coordinator's obligation for Spinning Reserve in the Zone in the Settlement Period for which it has not self-provided.

8.12.3 Non-Spinning Reserve.

The user rate per unit of purchased Non-Spinning Reserve for each Settlement Period in the Day-Ahead Market for each Zone shall be calculated by dividing the total capacity payments for Non-Spinning Reserve by the ISO's total MW purchases of Non-Spinning Reserve for that Settlement Period for that Zone which has not been self-provided by Scheduling Coordinators. The ISO will calculate the user rate for Non-Spinning Reserve in each Zone for each Settlement Period as:

$$NonSpRateDA(\$ / MW) = \frac{NonSpinPayDA}{NonSpinPurchDA}$$

where:

NonSpinPayDA = Total Non-Spinning Reserve payments for the Settlement Period in the Day-Ahead Market for the Zone.

NonSpinPurchDA = the total ISO Non-Spinning Reserve MW purchases for the Settlement Period for the Zone, excluding that which has been self-provided by Scheduling Coordinators.

For each Settlement Period, each Scheduling Coordinator shall pay to the ISO a sum calculated as follows for each Zone:

$$NonSpRateDA * NonSpinOblig$$

where *NonSpinOblig* is the Scheduling Coordinator's obligation for Non-Spinning Reserve in the Zone in the Settlement Period for which it has not self-provided.

8.12.3A Replacement Reserve.

The user rate per unit of Replacement Reserve obligation for each Settlement Period t for each Zone x shall be as follows:

$$ReplRate_{xt} = \frac{(PRepResDA_{xt} * OrigReplReqDA_{xt}) + (PRepResHA_{xt} * OrigReplReqHA_{xt})}{OrigReplReqDA_{xt} + OrigReplReqHA_{xt}}$$

where

$OrigReplReqDA_{xt}$ = Replacement Reserve requirement net of self-provision in the Day-Ahead Market before consideration of any substitutions pursuant to Section 8.2.3.6.

$OrigReplReqHA_{xt}$ = Incremental change in the Replacement Reserve requirement net of self-provision between the Day-Ahead Market and the Hour-Ahead Market before consideration of any substitutions pursuant to Section 8.2.3.6.

$PRepResDA_{xt}$ is the Market Clearing Price for Replacement Reserve in the Day-Ahead Market for Zone x in Settlement Period t .

$PRepResHA_{xt}$ is the Market Clearing Price for Replacement Reserve in the Hour-Ahead Market for Zone x in Settlement Period t .

For each Settlement Period t , each Scheduling Coordinator shall pay to the ISO a sum calculated as follows for each Zone x :

$$ReplRate_{xt} * ReplOblig_{jxt}$$

where

$$ReplOblig_{jxt} = DevReplOblig_{jxt} + RemRepl_{jxt} - SelfProv_{jxt} + NetInterSCTrades_{jxt}$$

$DevReplOblig_{jxt}$ is the Scheduling Coordinator's obligation for deviation Replacement Reserve in Zone x in the Settlement Period t and $RemRepl_{jxt}$ is the Scheduling Coordinator's obligation for remaining Replacement Reserve in Zone x for Settlement Period t .

$SelfProv_{jxt}$ is Scheduling Coordinator's Replacement Reserve self-provision in Zone x for Settlement Period t.

$NetInterSCTrades_{jxt}$ is the sale of Replacement Reserve less the purchase of Replacement Reserve through Inter-Scheduling Coordinator Trades by Scheduling Coordinator j in Zone x for Settlement Period t.

Deviation Replacement Reserve for Scheduling Coordinator j in Zone x for Settlement Period t is calculated as follows:

If $ReplObligTotal_{xt} > TotalDeviations_{xt}$ then:

$$DevReplOblig_{xjt} = \left[\text{Max} \left(0, \sum_i GenDev_{ijxt} \right) - \text{Min} \left(0, \sum_i LoadDev_{ijxt} \right) \right]$$

If $ReplObligTotal_{xt} < TotalDeviations_{xt}$ then:

$$DevReplOblig_{xjt} = \frac{ReplObligTotal_{xt}}{TotalDeviations_{xt}} * \left[\text{Max} \left(0, \sum_i GenDev_{ijxt} \right) - \text{Min} \left(0, \sum_i LoadDev_{ijxt} \right) \right]$$

where,

$$TotalDeviations_{xt} = \sum_j \left[\text{Max} \left(0, \sum_i GenDev_{ijxt} \right) - \text{Min} \left(0, \sum_i LoadDev_{ijxt} \right) \right]$$

$GenDev_{ijxt}$ = The deviation between scheduled and actual Energy Generation for Generator i represented by Scheduling Coordinator j in Zone x during Settlement Period t as referenced in Part D of Appendix N.

$LoadDev_{ijxt}$ = The deviation between scheduled and actual Load consumption for resource i represented by Scheduling Coordinator j in Zone x during Settlement Period t as referenced in Part D of Appendix N.

$DevReplOblig_{xt}$ is total deviation Replacement Reserve in Zone x for Settlement Period t.

$ReplObligTotal_{xt}$ is total Replacement Reserve Obligation in Zone x for Settlement Period t.

Remaining Replacement Reserve for Scheduling Coordinator j in Zone x for Settlement Period t is calculated as follows:

$$RemRepl_{xjt} = \frac{MeteredDemand_{jxt}}{TotalMeteredDemand_{xt}} * TotalRemRepl_{xt}$$

where:

$MeteredDemand_{jxt}$ is the Scheduling Coordinator's total metered Demand excluding exports in Zone x for Settlement Period t.

$TotalMeteredDemand_{xt}$ is total metered Demand excluding exports in Zone x for Settlement Period t.

$$TotalRemRepl_{xt} = Max[0, ReplObligTotal_{xt} + TotalSelfProv_{xt} - DevReplOblig_{xt}]$$

8.12.4 Voltage Support.

The short-term market Voltage Support user rate for Settlement Period t for Zone x shall be calculated as follows:

$$VSSTRate_{xt} = \frac{\sum_{i,j} VSST_{xijt}}{\sum_j QChargeVS_{xjt}}$$

$VSST_{xijt}$ = Voltage Support payment to Scheduling Coordinator j in respect of Generating Unit i in Zone x in the short-term market applicable to Settlement Period t.

$QChargeVS_{xjt}$ = charging quantity for Voltage Support for Scheduling Coordinator j for Settlement Period t in Zone x equal to the total metered Demand in Zone x (including exports to neighboring Control Areas and excluding metered Demand inside an MSS) by Scheduling Coordinator j for Settlement Period t.

The monthly long-term Voltage Support contract user rate for Settlement Period t for Zone x shall be calculated as follows:

$$VSLTRate_{xm} = \frac{\sum_{i,j} VSLT_{xijm}}{\sum_{jm} QChargeVS_{jt}}$$

where:

$VSLT_{xijm}$ = long-term Voltage Support contract payment to Scheduling Coordinator j for owner of Reliability Must-Run Unit i in Zone x for month m.

The short-term market Voltage Support charges for Settlement Period t payable by Scheduling Coordinator j will be calculated as follows:

$$VSSTCharge_{jt} = VSSTRate_t * QChargeVS_{jt}$$

where $VSSTCharge_{jt}$ is the amount payable by Scheduling Coordinator j for short-term market Voltage Support for Settlement Period t.

$VSSTRate_t$ is the short-term market Voltage Support user rate for Settlement Period t. The monthly long-term Voltage Support contract charge for month m payable by Scheduling Coordinator j will be calculated as follows:

$$VSLTCharge_m = VSLTRate_m * \sum_m QChargeVS_{jt}$$

where $VSLTCharge_m$ is the amount payable by Scheduling Coordinator j for long-term Voltage Support for month m.

$VSLTRate_m$ is the monthly long-term Voltage Support contract user rate charged by the ISO to Scheduling Coordinators for month m.

8.12.5 Black Start.

$QChargeBlackstart_{jt}$ = charging quantity for Black Start for Scheduling Coordinator j for Settlement Period t equal to the total metered Demand (excluding exports to neighboring Control Areas and metered Demand of a MSS) by Scheduling Coordinator j for Settlement Period t.

The Black Start Energy payment user rate for Settlement Period t will be calculated as follows:

$$BSRate_t = \frac{\sum_{i,j} BSEn_{ijt}}{\sum_j QChargeBlackstart_{jt}}$$

where $BSEn_{ijt}$ is the ISO payment to Scheduling Coordinator j for owner of Reliability Must-Run Unit (or to Black Start Generator j, as the case may be) for Generating Unit i providing Black Start Energy in Settlement Period t.

The Black Start Energy user charge for Settlement Period t for Scheduling Coordinator j will be calculated as follows:

$$BSCharge_{jt} = BSRate_t * QChargeBlackStart_{jt}$$

8.13 Temporary Changes To Ancillary Services Penalties.

8.13.1 Application and Termination.

The temporary change, respecting Ancillary Services penalties, set out in Section 8.13.2 shall continue in effect until such time as the Chief Executive Officer of the ISO issues a Notice of Full-Scale Operations, posted on the ISO Internet "Home Page", at <http://www.ISO.com>, or such other Internet address as the ISO may publish from time to time, specifying the date on which this Section 8.13 shall cease to apply, which date shall be not less than seven (7) days after the Notice of Full-Scale Operations is issued.

8.13.2 For so long as this Section 8.13.2 remains in effect, Scheduling Coordinators shall not be liable for the penalties specified in Section 8.10.2 of the ISO Tariff if, as a result of limitations associated with the ISO's Congestion Management software, the scheduled output of the resource from which the Scheduling Coordinator has committed to provide an Ancillary Service is adjusted by the ISO to a level

that conflicts with the Scheduling Coordinator's Ancillary Service capacity commitments, thereby resulting in a failed availability test.

8.14 Temporary Rule Limiting Adjustment Bids Applicable To Dispatchable Loads And Exports.

8.14.1 Application and Termination.

The temporary change limiting Adjustment Bids for Dispatchable Loads and exports set out in Section 8.14.2 shall continue in effect until such time as the Chief Executive Officer of the ISO posts a notice ("Notice of Full-Scale Operations"), on the ISO Home Page specifying the date on which this Section 8.14 shall cease to apply, which date shall not be less than seven (7) days after the Notice of Full-Scale Operations is posted.

8.14.2 For so long as this Section 8.14.2 remains in effect, Scheduling Coordinators shall continue to be allowed to specify Adjustment Bids for Dispatchable Loads and exports, conditioned on the rule that the last segment of the Adjustment Bid (i.e., the maximum MW value) must equal the preferred MW operating point specified for the Dispatchable Load or export.

9. OUTAGES.

9.1 Coordination and Approval for Outages.

The ISO shall have authority to coordinate and approve Outages and returns to service of all facilities comprised in the ISO Controlled Grid and Reliability Must-Run Units in accordance with Section 9.3. The ISO will coordinate and approve Maintenance Outages and coordinate responses to Forced Outages of all transmission facilities in the ISO Controlled Grid and Reliability Must-Run Units in accordance with this Section 9. Any scheduled Outages that are cancelled by ISO real-time operations due to system requirements must be rescheduled with the ISO Outage Coordination Department in accordance with Section 9.3.